

Achieving Compositionality of the Stable Model Semantics for SMODELS Programs *

EMILIA OIKARINEN and TOMI JANHUNEN

Helsinki University of Technology TKK

Department of Information and Computer Science

P.O. Box 5400, FI-02015 TKK, Finland

Emilia.Oikarinen@tkk.fi, Tomi.Janhunen@tkk.fi

submitted 29 February 2008; accepted 25 September 2008

Abstract

In this paper, a Gaifman-Shapiro-style module architecture is tailored to the case of SMODELS programs under the stable model semantics. The composition of SMODELS program modules is suitably limited by module conditions which ensure the compatibility of the module system with stable models. Hence the semantics of an entire SMODELS program depends directly on stable models assigned to its modules. This result is formalized as a *module theorem* which truly strengthens Lifschitz and Turner's splitting-set theorem (1994) for the class of SMODELS programs. To streamline generalizations in the future, the module theorem is first proved for normal programs and then extended to cover SMODELS programs using a translation from the latter class of programs to the former class. Moreover, the respective notion of module-level equivalence, namely *modular equivalence*, is shown to be a proper congruence relation: it is preserved under substitutions of modules that are modularly equivalent. Principles for program decomposition are also addressed. The strongly connected components of the respective dependency graph can be exploited in order to extract a module structure when there is no explicit a priori knowledge about the modules of a program. The paper includes a practical demonstration of tools that have been developed for automated (de)composition of SMODELS programs.

KEYWORDS: answer set programming, module system, compositional semantics, stable model semantics, modular equivalence

1 Introduction

Answer set programming (ASP) (Niemelä 1999; Marek and Truszczyński 1999; Gelfond and Leone 2002; Baral 2003) is an approach to declarative rule-based constraint programming that has been successively used in many knowledge representation and reasoning tasks (Soininen et al. 2001; Nogueira et al. 2001; Erdem et al. 2006; Brooks et al. 2007). In ASP, the problem at hand is solved declaratively

* This is an extended version of two conference papers (Oikarinen and Janhunen 2006; Oikarinen 2007) presented at ECAI'06 and LPNMR'07, respectively.

1. by writing down a logic program the answer sets of which correspond to the solutions of the problem and
2. by computing the answer sets of the program using a special purpose search engine that has been designed for this task.

A modelling philosophy of this kind suggests to treat programs as integral entities. The answer set semantics—originally defined for entire programs only (Gelfond and Lifschitz 1988; Gelfond and Lifschitz 1990)—reflects also this fact. Such indivisibility of programs is creating an increasing problem as program instances tend to grow along the demands of new application areas of ASP. It is to be expected that prospective application areas such as semantic web, bioinformatics, and logical cryptanalysis will provide us with huge program instances to create, to solve, and to maintain.

Modern programming languages provide means to exploit *modularity* in a number of ways to govern the complexity of programs and their development process. Indeed, the use of *program modules* or *objects* of some kind can be viewed as an embodiment of the classical *divide-and-conquer* principle in the art of programming. The benefits of modular program development are numerous. A software system is much easier to design as a set of interacting components rather than a monolithic system with unclear internal structure. A modular design lends itself better for implementation as programming tasks are then easier to delegate amongst the team of programmers. It also enables the re-use of code organized as module libraries, for instance. To achieve similar advantages in ASP, one of the central goals of our research is to foster modularity in the context of ASP.

Although modularity has been studied extensively in the context of conventional logic programs, see Bugliesi et al. (1994) for a survey, relatively little attention has been paid to modularity in ASP. Many of the approaches proposed so far are based on very strict syntactic conditions on the module hierarchy, for instance, by enforcing stratification of some kind, or by prohibiting recursion altogether (Eiter et al. 1997; Tari et al. 2005; Eiter et al. 1997). On the other hand, approaches based on *splitting-sets* (Lifschitz and Turner 1994; Eiter et al. 1997; Faber et al. 2005) are satisfactory from the point of view of *compositional semantics*: the answer sets of an entire program are obtained as specific combinations of the answer sets of its components. A limitation of splitting-sets is that they divide logic programs in two parts, the *top* and the *bottom*, which is rather restrictive and conceptually very close to stratification. On the other hand, the compositionality of answer set semantics is neglected altogether in syntactic approaches (Ianni et al. 2004; Tari et al. 2005) and this aspect of models remains completely at the programmer’s responsibility.

To address the deficiencies described above, we accommodate a module architecture proposed by Gaifman-Shapiro (1989) to answer set programming, and in particular, in the context of the SMOELS system (Simons et al. 2002).¹ There are two main criteria for the design. First of all, it is essential to establish the full compositionality of answer set semantics with respect to the module system. This is to

¹ Also other systems such as CLASP (Gebser et al. 2007) and CMOELS (Lierler 2005) that are compatible with the internal file format of the SMOELS system are implicitly covered.

ensure that various reasoning tasks—such as the verification of program equivalence (Janhunen and Oikarinen 2007)—can be modularized. Second, for the sake of flexibility of knowledge representation, any restrictions on the module hierarchy should be avoided as far as possible. We pursue these goals according to the following plan.

In Section 2, we take a closer look at modularity in the context of logic programming. In order to enable comparisons later on, we also describe related approaches in the area of ASP in more detail. The technical preliminaries of the paper begin with a recapitulation of *stable model semantics* (Gelfond and Lifschitz 1988) in Section 3. However, stable models, or answer sets, are reformulated for a class of programs that corresponds to the input language of the SMOLELS solver (Simons et al. 2002). The definition of *splitting-sets* is included to enable a detailed comparison with our results. Moreover, we introduce the concepts of *program completion* and *loop formulas* to be exploited in proofs later on, and review some notions of equivalence that have been proposed in the literature.

In Section 4, we present a *module architecture* for SMOLELS programs, in which the interaction between modules takes place through a clearly defined *input/output interface*. The design superficially resembles that of Gaifman and Shapiro (1989) but in order to achieve the full compositionality of stable models, further conditions on program composition are incorporated. This is formalized as the main result of the paper, namely the *module theorem*, which goes beyond the splitting-set theorem (Lifschitz and Turner 1994) as *negative recursion* is tolerated by our definitions. The proof is first presented for normal programs and then extended for SMOLELS programs using a translation-based scheme. The scheme is based on three distinguished properties of translations, *strong faithfulness*, *preservation of compositions*, and *modularity*, that are sufficient to lift the module theorem. In this way, we get prepared for even further syntactic extensions of the module theorem in the future. The respective notion of module-level equivalence, that is, *modular equivalence*, is proved to be a proper *congruence* for program composition. In other words, substitutions of modularly equivalent modules preserve modular equivalence. This way modular equivalence can be viewed as a reasonable compromise between *uniform equivalence* (Eiter and Fink 2003) which is not a congruence for program union, and *strong equivalence* (Lifschitz et al. 2001) which is a congruence for program union but allows only rather straightforward semantics-preserving transformations of (sets of) rules.

In Section 5, we address principles for the decomposition of SMOLELS programs. It turns out that strongly connected components of dependency graphs can be exploited in order to extract a module structure when there is no explicit a priori knowledge about the modules of a program. In addition, we consider the possibility of relaxing our restrictions on program composition using the content of the module theorem as a criterion. The result is that the notion of modular equivalence remains unchanged but the computational cost of checking legal compositions of modules becomes essentially higher. In Section 6, we demonstrate how the module system can be exploited in practise in the context of the SMOLELS system. We present tools that have been developed for (de)composition of logic programs and conduct a practical experiment which illustrates the performance of the tools when processing

very large benchmark instances, that is, SMOLETS programs having up to millions of rules. The concluding remarks of this paper are presented in Section 7.

2 Modularity aspects of logic programming

Bugliesi et al. (1994) address several properties that are expected from a modular logic programming language. For instance, a modular language should

- allow *abstraction*, *parameterization*, and *information hiding*,
- *ease program development* and *maintenance* of large programs,
- allow *re-usability*,
- have a *non-trivial notion of program equivalence* to justify replacement of program components, and
- maintain the *declarativity* of logic programming.

Two mainstream programming disciplines are identified. In *programming-in-the-large* approaches programs are composed with algebraic operators, see for instance (O’Keefe 1985; Mancarella and Pedreschi 1988; Gaifman and Shapiro 1989; Brogi et al. 1994). In *programming-in-the-small* approaches abstraction mechanisms are used, see for instance (Miller 1989; Giordano and Martelli 1994).

The *programming-in-the-large* approaches have their roots in the framework proposed by O’Keefe (1985) where logic programs are seen as *elements of an algebra* and the operators for *composing programs* are seen as *operators in that algebra*. The fundamental idea is that a logic program should be understood as a part of a system of programs. Program composition is a powerful tool for structuring programs without any need to extend the underlying language of Horn clauses. Several algebraic operations such as *union*, *deletion*, *overriding union* and *closure* have been considered. This approach *supports* naturally the *re-use* of the pieces of programs in different composite programs, and when combined with an adequate equivalence relation also the replacement of equivalent components. This approach is highly flexible, as new composition mechanisms can be obtained by introducing a corresponding operator in the algebra or combining existing ones. Encapsulation and information hiding can be obtained by introducing suitable *interfaces* for components.

The *programming-in-the-small* approaches originate from (Miller 1989). In this approach the composition of modules is modelled in terms of logical connectives of a language that is defined as an *extension of Horn clause logic*. The approach in (Giordano and Martelli 1994) employs the same structural properties, but suggests a more refined way of modelling visibility rules than the one in (Miller 1989).

It is essential that a semantical characterization of a modular language is such that the meaning of composite programs can be defined in terms of the meaning of its components (Maher 1993). To be able to identify when it is safe to substitute a module with another without affecting the global behavior it is crucial to have a notion of *semantical equivalence*. More formally these desired properties can be described under the terms of *compositionality* and *full abstraction* (Gaifman and Shapiro 1989; Meyer 1988).

Two programs are *observationally congruent*, if and only if they exhibit the same observational behavior in every *context* they can be placed in. A semantics is compositional if semantical equality implies observational congruence, and fully abstract if semantical equivalence coincides with observational congruence. The compositionality and full abstraction properties for different notions of semantical equivalence (*subsumption equivalence*, *logical equivalence*, and *minimal Herbrand model equivalence*) and different operators in an algebra (union, closure, overriding union) are considered in (Bugliesi et al. 1994). It is worth noting that minimal Herbrand model equivalence coincides with the *weak equivalence* relation for positive logic programs. As to be defined in Section 3.3, two logic programs are weakly equivalent if and only if they have exactly the same answer sets. As the equivalence based on minimal Herbrand model semantics is not compositional with respect to program union (Bugliesi et al. 1994), we note that it is not a suitable composition operator for our purposes unless further constraints are introduced.

2.1 Modularity in answer set programming

There are a number of approaches within answer set programming involving modularity in some sense, but only a few of them really describe a flexible module architecture with a clearly defined interface for module interaction.

Eiter, Gottlob, and Veith (1997) address modularity in ASP in the programming-in-the-small sense. They view program modules as *generalized quantifiers* as introduced in (Mostowski 1957). The definitions of quantifiers are allowed to nest, that is, program P can refer to another module Q by using it as a generalized quantifier. The main program is clearly distinguished from subprograms, and it is possible to nest calls to submodules if the so-called *call graph* is *hierarchical*, that is, *acyclic*. Nesting, however, increases the computational complexity depending on the depth of nesting.

Ianni et al. (2004) propose another programming-in-the-small approach to ASP based on *templates*. The semantics of programs containing template atoms is determined by an *explosion algorithm*, which basically replaces the template with a standard logic program. However, the explosion algorithm is not guaranteed to terminate if template definitions are used recursively.

Tari et al. (2005) extend the language of normal logic programs by introducing the concept of *import rules* for their ASP program modules. There are three types of import rules which are used to import a set of tuples $\overline{X}$ for a predicate q from another module. An *ASP module* is defined as a quadruple of a module name, a set of parameters, a collection of normal rules and a collection of import rules. Semantics is only defined for modular programs with acyclic dependency graph, and answer sets of a module are defined with respect to the modular ASP program containing it. Also, it is required that import rules referring to the same module always have the same form.

Programming-in-the-large approaches in ASP are mostly based on Lifschitz and Turner's splitting-set theorem (Lifschitz and Turner 1994) or are variants of it. The class of logic programs considered in (Lifschitz and Turner 1994) is that of *extended*

disjunctive logic programs, that is, disjunctive logic programs with two kinds of negation. A *component structure* induced by a *splitting sequence*, that is, iterated splittings of a program, allows a bottom-up computation of answer sets. The restriction implied by this construction is that the dependency graph of the component chain needs to be acyclic.

Eiter, Gottlob, and Mannila (1997) consider *disjunctive logic programs as a query language for relational databases*. A query program π is instantiated with respect to an input database D confined by an input schema $\mathbf{R}$. The semantics of π determines, for example, the answer sets of $\pi[D]$ which are projected with respect to an output schema $\mathbf{S}$. Their module architecture is based on both *positive and negative dependencies* and no recursion between modules is tolerated. These constraints enable a straightforward generalization of the splitting-set theorem for the architecture.

Faber et al. (2005) apply the *magic set method* in the evaluation of *Datalog programs with negation*, that is, effectively normal logic programs. This involves the concept of an *independent set* S of a program P which is a specialization of a splitting set. Due to a close relationship with splitting sets, the flexibility of independent sets for parceling programs is limited in the same way.

The approach based on *lp-functions* (Gelfond and Gabaldon 1999; Baral 2003) is another programming-in-the-large approach. An lp-function has an interface based on input and output signatures. Several operations, for instance *incremental extension*, *interpolation*, *input opening*, and *input extension*, are introduced for composing and refining lp-functions. The composition of lp-functions, however, only allows incremental extension, and thus similarly to the splitting-set theorem there can be no recursion between lp-functions.

3 Preliminaries: SMOLETS programs

To keep the presentation of our module architecture compatible with an actual implementation, we cover the input language of the SMOLETS system—excluding *optimization statements*. In this section we introduce the syntax and semantics for SMOLETS programs, and, in addition, point out a number of useful properties of logic programs under stable model semantics. We end this section with a review of equivalence relations that have been proposed for logic programs.

3.1 Syntax and semantics

Basic constraint rules (Simons et al. 2002) are either *weight rules* of the form

$$a \leftarrow w \leq \{b_1 = w_{b_1}, \dots, b_n = w_{b_n}, \sim c_1 = w_{c_1}, \dots, \sim c_m = w_{c_m}\} \quad (1)$$

or *choice rules* of the form

$$\{a_1, \dots, a_h\} \leftarrow b_1, \dots, b_n, \sim c_1, \dots, \sim c_m \quad (2)$$

where a , a_i 's, b_j 's, and c_k 's are atoms, $h > 0$, $n \geq 0$, $m \geq 0$, and $\sim$ denotes *negation as failure* or *default negation*. In addition, a weight rule (1) involves a weight limit

$w \in \mathbb{N}$ and the respective weights $w_{b_j} \in \mathbb{N}$ and $w_{c_k} \in \mathbb{N}$ associated with each *positive literal* b_j and *negative literal* $\sim c_k$. We use a shorthand $\sim A = \{\sim a \mid a \in A\}$ for any set of atoms A . Each basic constraint rule r consists of two parts: a or $\{a_1, \dots, a_h\}$ is the *head* of the rule, denoted by $\text{Head}(r)$, whereas the rest is called its *body*. The set of atoms appearing in a body of a rule can be further divided into the set of *positive body atoms*, defined as $\text{Body}^+(r) = \{b_1, \dots, b_n\}$, and the set of *negative body atoms*, defined as $\text{Body}^-(r) = \{c_1, \dots, c_m\}$. We denote by $\text{Body}(r) = \text{Body}^+(r) \cup \text{Body}^-(r)$ the set of atoms appearing in the body of a rule r . Roughly speaking, the body gives the conditions on which the head of the rule must be satisfied. For example, in case of a choice rule (2), this means that any head atom a_i can be inferred to be true if $b_1, \dots, b_n$ hold true by some other rules but none of the atoms $c_1, \dots, c_m$. Weight rules of the form (1) cover many other kinds of rules of interest as their special cases:

$$a \leftarrow l \leq \{b_1, \dots, b_n, \sim c_1, \dots, \sim c_m\} \quad (3)$$

$$a \leftarrow b_1, \dots, b_n, \sim c_1, \dots, \sim c_m \quad (4)$$

$$\leftarrow b_1, \dots, b_n, \sim c_1, \dots, \sim c_m \quad (5)$$

$$\text{compute } \{b_1, \dots, b_n, \sim c_1, \dots, \sim c_m\} \quad (6)$$

Cardinality rules of the form (3) are essentially weight rules (1) where $w = l$ and all weights associated with literals equal to 1. A *normal rule*, or alternatively a *basic rule* (4) is a special case of a cardinality rule (3) with $l = n + m$. The intuitive meaning of an integrity constraint (5) is that the conditions given in the body are never simultaneously satisfied. The same can be stated in terms of a basic rule $f \leftarrow b_1, \dots, b_n, \sim c_1, \dots, \sim c_m, \sim f$ where f is a new atom dedicated to integrity constraints. Finally, *compute statements* (6) of the SMOLELS system effectively correspond to sets of integrity constraints $\leftarrow \sim b_1, \dots, \leftarrow \sim b_n$ and $\leftarrow c_1, \dots, \leftarrow c_m$.

Because the order of literals in (1) and (2) is considered irrelevant, we introduce shorthands $A = \{a_1, \dots, a_h\}$, $B = \{b_1, \dots, b_n\}$, and $C = \{c_1, \dots, c_m\}$ for the sets of atoms involved in rules, and $W_B = \{w_{b_1}, \dots, w_{b_n}\}$ and $W_C = \{w_{c_1}, \dots, w_{c_m}\}$ for the respective sets of weights in (1). Using these notations (1) and (2) are abbreviated by $a \leftarrow w \leq \{B = W_B, \sim C = W_C\}^2$ and $\{A\} \leftarrow B, \sim C$.

In the SMOLELS system, the internal representation of programs is based on rules of the forms (1)–(4) and (6) and one may conclude that basic constraint rules, as introduced above, provide a reasonable coverage of SMOLELS programs. Thus we concentrate on rules of the forms (1) and (2) and view others as syntactic sugar in the sequel.

Definition 3.1 *An SMOLELS program P is a finite set of basic constraint rules.*

An SMOLELS program consisting only of basic rules is called a *normal logic program* (NLP), and a basic rule with an empty body is called a *fact*. Given an SMOLELS

² Strictly speaking $B = W_B$ and $\sim C = W_C$ are to be understood as sets of pairs of the form (b, w_b) and $(\sim c, w_c)$, respectively. For convenience the exact matching between literals and weights is left implicit in the shorthand.

program P , we write $\text{At}(P)$ for its *signature*, that is, the set of atoms occurring in P , and $\text{Body}(P)$ and $\text{Head}(P)$ for the respective subsets of $\text{At}(P)$ having *body occurrences* and *head occurrences* in the rules of P . Furthermore, $\text{Choices}(P) \subseteq \text{Head}(P)$ denotes the set of atoms having a head occurrence in a choice rule of P .

Given a program P , an *interpretation* M of P is a subset of $\text{At}(P)$ defining which atoms $a \in \text{At}(P)$ are *true* ($a \in M$) and which are *false* ($a \notin M$). A weight rule (1) is satisfied in M if and only if $a \in M$ whenever the sum of weights

$$\sum_{b \in B \cap M} w_b + \sum_{c \in C \setminus M} w_c$$

is at least w . A choice rule $\{A\} \leftarrow B, \sim C$ is always satisfied in M . An interpretation $M \subseteq \text{At}(P)$ is a (classical) model of P , denoted by $M \models P$, if and only if M satisfies all the rules in P .

The generalization of the *Gelfond-Lifschitz reduct* (Gelfond and Lifschitz 1988) for SMOLELS programs is defined as follows.

Definition 3.2 *For an SMOLELS program P and an interpretation $M \subseteq \text{At}(P)$, the reduct P^M contains*

1. *a rule $a \leftarrow B$ if and only if there is a choice rule $\{A\} \leftarrow B, \sim C$ in P such that $a \in A \cap M$, and $M \cap C = \emptyset$;*
2. *a rule $a \leftarrow w' \leq \{B = W_B\}$ if and only if there is a weight rule $a \leftarrow w \leq \{B = W_B, \sim C = W_C\}$ in P such that $w' = \max(0, w - \sum_{c \in C \setminus M} w_c)$.*

We say that an SMOLELS program P is *positive* if each rule in P is a weight rule restricted to the case $C = \emptyset$. Recalling that the basic rules are just a special case of weight rules, we note that the reduct P^M is always positive. An interpretation $M \subseteq \text{At}(P)$ is the *least model* of a positive SMOLELS program P , denoted by $\text{LM}(P)$, if and only if $M \models P$ and there is no $M' \models P$ such that $M' \subset M$. Given the *least model semantics* for positive programs (Janhunen and Oikarinen 2007), the stable model semantics (Gelfond and Lifschitz 1988) straightforwardly generalizes for SMOLELS programs (Simons et al. 2002).

Definition 3.3 *An interpretation $M \subseteq \text{At}(P)$ is a stable model of an SMOLELS program P if and only if $M = \text{LM}(P^M)$.*

Given an SMOLELS program P and $a, b \in \text{At}(P)$, we say that a *depends directly* on b , denoted by $b \leq_1 a$, if and only if P contains a rule r such that $a \in \text{Head}(r)$ and $b \in \text{Body}^+(r)$. The *positive dependency graph* of P , denoted by $\text{Dep}^+(P)$, is the graph $\langle \text{At}(P), \leq_1 \rangle$. The reflexive and transitive closure of $\leq_1$ gives rise to the dependency relation $\leq$ over $\text{At}(P)$. A *strongly connected component* (SCC) S of $\text{Dep}^+(P)$ is a maximal set $S \subseteq \text{At}(P)$ such that $b \leq a$ holds for every $a, b \in S$.

3.2 Splitting sets and loop formulas

In this section we consider only the class of *normal logic programs*. We formulate the *splitting-set theorem* (Lifschitz and Turner 1994) in the case of normal

logic programs³, and give an alternative definition of stable models based on the *classical models* of the *completion* of a program (Clark 1978) and its *loop formulas* (Lin and Zhao 2004). The splitting-set theorem can be used to simplify the computation of stable models by splitting a program into parts, and it is also a useful tool for structuring mathematical proofs for properties of logic programs.

Definition 3.4 *A splitting set for a normal logic program P is any set $U \subseteq \text{At}(P)$ such that for every rule r in P it holds that $\text{At}(r) \subseteq U$ if $\text{Head}(r) \in U$.*

The set of rules $r \in P$ such that $\text{At}(r) \subseteq U$ is the *bottom* of P relative to U , denoted by $\text{b}_U(P)$. The set $\text{t}_U(P) = P \setminus \text{b}_U(P)$ is the *top* of P relative to U which can be partially evaluated with respect to an interpretation $X \subseteq U$. The result is a program $\text{e}(\text{t}_U(P), X)$ defined as

$$\begin{aligned} \{\text{Head}(r) \leftarrow (\text{Body}^+(r) \setminus U), \sim(\text{Body}^-(r) \setminus U) \mid r \in \text{t}_U(P), \\ \text{Body}^+(r) \cap U \subseteq X \text{ and } (\text{Body}^-(r) \cap U) \cap X = \emptyset\}. \end{aligned}$$

A *solution* to a program with respect to a splitting set is a pair consisting of a stable model X for the bottom and a stable model Y for the top partially evaluated with respect to X .

Definition 3.5 *Given a splitting set U for a normal logic program P , a solution to P with respect to U is a pair $\langle X, Y \rangle$ such that*

- (i) $X \subseteq U$ is a stable model of $\text{b}_U(P)$, and
- (ii) $Y \subseteq \text{At}(P) \setminus U$ is a stable model of $\text{e}(\text{t}_U(P), X)$.

Solutions and stable models relate as follows.

Theorem 3.6 (The splitting-set theorem (Lifschitz and Turner 1994))

Let U be a splitting set for a normal logic program P and $M \subseteq \text{At}(P)$ an interpretation. Then $M \in \text{SM}(P)$ if and only if the pair $\langle M \cap U, M \setminus U \rangle$ is a solution to P with respect to U .

The splitting-set theorem can also be used in an iterative manner, if there is a *monotone sequence* of splitting sets $\{U_1, \dots, U_i, \dots\}$, that is, $U_i \subset U_j$ if $i < j$, for program P . This is called a *splitting sequence* and it induces a *component structure* for P . The splitting-set theorem generalizes to a *splitting sequence theorem* (Lifschitz and Turner 1994), and given a splitting sequence, the stable models of a program P can be computed iteratively bottom-up.

Lin and Zhao present an alternative definition of stable models for normal logic programs based on the *classical models* of the *completion* of a program (Clark 1978) and its *loop formulas* (Lin and Zhao 2004). We will apply this definition later on in the proof of the module theorem (Theorem 4.14).

³ Lifschitz and Turner (1994) consider a more general class of logic programs, *extended disjunctive logic programs*, that is, disjunctive logic programs with two kinds of negation.

Definition 3.7 (Program completion (Clark 1978; Fages 1994)) *The completion of a normal logic program P is*

$$\text{Comp}(P) = \bigwedge_{a \in \text{At}(P)} \left(a \leftrightarrow \bigvee_{\text{Head}(r)=a} \left(\bigwedge_{b \in \text{Body}^+(r)} b \wedge \bigwedge_{c \in \text{Body}^-(r)} \neg c \right) \right). \quad (7)$$

Note that an empty body reduces to true and in that case the respective equivalence for an atom a is logically equivalent to $a \leftrightarrow \top$.

Definition 3.8 *Given a normal logic program P , a set of atoms $L \subseteq \text{At}(P)$ is a loop of P if for every $a, b \in L$ there is a path of non-zero length from a to b in $\text{Dep}^+(P)$ such that all vertices in the path are in L .*

Definition 3.9 *Given a normal logic program P and a loop $L \subseteq \text{At}(P)$ of P , the loop formula associated with L is*

$$\text{LF}(L, P) = \neg \left(\bigvee_{r \in \text{EB}(L, P)} \left(\bigwedge_{b \in \text{Body}^+(r)} b \wedge \bigwedge_{c \in \text{Body}^-(r)} \neg c \right) \right) \rightarrow \bigwedge_{a \in L} \neg a$$

where $\text{EB}(L, P) = \{r \in P \mid \text{Head}(r) \in L \text{ and } \text{Body}^+(r) \cap L = \emptyset\}$ is the set of rules in P which have external bodies of L .

Now, stable models of a program and classical models of its completion that satisfy the loop formulas relate as follows.

Theorem 3.10 ((Lin and Zhao 2004)) *Given a normal logic program P and an interpretation $M \subseteq \text{At}(P)$, $M \in \text{SM}(P)$ if and only if $M \models \text{Comp}(P) \cup \text{LF}(P)$, where $\text{LF}(P)$ is the set of all loop formulas associated with the loops of P .*

3.3 Equivalence relations for SMOLELS programs

There are several notions of equivalence that have been proposed for logic programs. We review a number of them in the context of SMOLELS programs.

Lifschitz et al. (2001) address the notions of *weak/ordinary equivalence* and *strong equivalence*.

Definition 3.11 *SMOLELS programs P and Q are weakly equivalent, denoted by $P \equiv Q$, if and only if $\text{SM}(P) = \text{SM}(Q)$; and strongly equivalent, denoted by $P \equiv_s Q$, if and only if $P \cup R \equiv Q \cup R$ for any SMOLELS program R .*

The program R in the above definition can be understood as an arbitrary context in which the two programs being compared could be placed. Therefore strongly equivalent logic programs are semantics preserving substitutes of each other and relation $\equiv_s$ is a *congruence relation* for $\cup$ among SMOLELS programs, that is, if $P \equiv_s Q$, then also $P \cup R \equiv_s Q \cup R$ for all SMOLELS programs R . Using $R = \emptyset$ as context, one sees that $P \equiv_s Q$ implies $P \equiv Q$. The converse does not hold in general.

A way to weaken strong equivalence is to restrict possible contexts to sets of facts. The notion of *uniform equivalence* has its roots in the database community (Sagiv 1987), see (Eiter and Fink 2003) for the case of the stable model semantics.

Definition 3.12 *SMODELS programs P and Q are uniformly equivalent, denoted by $P \equiv_u Q$, if and only if $P \cup F \equiv Q \cup F$ for any set of facts F .*

Example 3.13 shows that uniform equivalence is not a congruence for union.

Example 3.13 ((Eiter et al. 2004, Example 1)) *Consider programs $P = \{a.\}$ and $Q = \{a \leftarrow \sim b. a \leftarrow b.\}$. It holds that $P \equiv_u Q$, but $P \cup R \not\equiv Q \cup R$ for the context $R = \{b \leftarrow a.\}$. This implies $P \not\equiv_s Q$ and $P \cup R \not\equiv_u Q \cup R$. ■*

There are also *relativized variants of strong and uniform equivalence* (Woltran 2004) which allow the context to be constrained using a set of atoms A .

For weak equivalence of programs P and Q to hold, $\text{SM}(P)$ and $\text{SM}(Q)$ have to be identical subsets of $2^{\text{At}(P)}$ and $2^{\text{At}(Q)}$, respectively. The same effect can be seen with $P \equiv_s Q$ and $P \equiv_u Q$. This makes these relations less useful if $\text{At}(P)$ and $\text{At}(Q)$ differ by some (local) atoms not trivially false in all stable models. The *visible equivalence relation* (Janhunen 2006) takes the interfaces of programs into account. The atoms in $\text{At}(P)$ are partitioned into two parts, $\text{At}_v(P)$ and $\text{At}_h(P)$, which determine the *visible* and the *hidden* parts of $\text{At}(P)$, respectively. Visible atoms form an interface for interaction between programs, and hidden atoms are local to each program and thus negligible when visible equivalence of programs is concerned.

Definition 3.14 *SMODELS programs P and Q are visibly equivalent, denoted by $P \equiv_v Q$, if and only if $\text{At}_v(P) = \text{At}_v(Q)$ and there is a bijection $f : \text{SM}(P) \rightarrow \text{SM}(Q)$ such that for all $M \in \text{SM}(P)$, $M \cap \text{At}_v(P) = f(M) \cap \text{At}_v(Q)$.*

Note that the number of stable models is also preserved under $\equiv_v$. Such a strict correspondence of models is much dictated by the answer set programming methodology: the stable models of a program usually correspond to the solutions of the problem being solved and thus the exact preservation of models is highly significant. In the fully visible case, that is, for $\text{At}_h(P) = \text{At}_h(Q) = \emptyset$, the relation $\equiv_v$ becomes very close to $\equiv$. The only difference is the requirement that $\text{At}(P) = \text{At}(Q)$ insisted on $\equiv_v$. This is of little importance as $\text{At}(P)$ can always be extended by adding (tautological) rules of the form $a \leftarrow a$ to P without affecting the stable models of the program. Since weak equivalence is not a congruence for $\cup$, visible equivalence cannot be a congruence for program union either.

The verification of weak, strong, or uniform equivalence is a **coNP**-complete decision problem for SMODELS programs (Marek and Truszczyński 1991; Pearce et al. 2001; Eiter and Fink 2003). The computational complexity of deciding $\equiv_v$ is analyzed in (Janhunen and Oikarinen 2007). If the use of hidden atoms is not limited in any way, the problem of verifying visible equivalence becomes at least as hard as the counting problem **#SAT** which is **#P**-complete (Valiant 1979). It is possible, however, to govern the computational complexity by limiting the use of hidden atoms

by the property of having *enough visible atoms* (Janhunen and Oikarinen 2007). Intuitively, if P has enough visible atoms, the EVA property for short, then each interpretation of $\text{At}_v(P)$ *uniquely* determines an interpretation of $\text{At}_h(P)$. Consequently, the stable models of P can be distinguished on the basis of their visible parts. Although verifying the EVA property can be hard in general (Janhunen and Oikarinen 2007, Proposition 4.14), there are syntactic subclasses of SMOLETS programs with the EVA property. The use of visible atoms remains unlimited and thus the full expressiveness of SMOLETS programs remains at programmer's disposal. Also note that the EVA property can always be achieved by declaring sufficiently many atoms visible. For SMOLETS programs with the EVA property, the verification of visible equivalence is a **coNP**-complete decision problem (Janhunen and Oikarinen 2007).

Eiter et al. (2005) introduce a very general framework based on *equivalence frames* to capture various kinds of equivalence relations. All the equivalence relations defined in this section can be defined using the framework. Visible equivalence, however, is exceptional in the sense that it does not fit into equivalence frames based on *projected answer sets*. As a consequence, the number of answer sets may not be preserved which is somewhat unsatisfactory because of the general nature of answer set programming as discussed in the previous section. Under the EVA assumption, however, the *projective variant of visible equivalence* defined by

$$\{M \cap \text{At}_v(P) \mid M \in \text{SM}(P)\} = \{N \cap \text{At}_v(Q) \mid N \in \text{SM}(Q)\}$$

coincides with visible equivalence.

Recently Woltran presented another general framework characterizing $\langle \mathcal{H}, \mathcal{B} \rangle$ -*equivalence* (Woltran 2007). $\langle \mathcal{H}, \mathcal{B} \rangle$ -equivalence is defined similarly to strong equivalence, but the set of possible contexts is restricted by limiting the head and body occurrences of atoms in a context program R by $\mathcal{H}$ and $\mathcal{B}$, respectively. Thus, programs P and Q are $\langle \mathcal{H}, \mathcal{B} \rangle$ -equivalent if and only if $P \cup R \equiv Q \cup R$ for all R such that $\text{Head}(R) \subseteq \mathcal{H}$ and $\text{Body}(R) \subseteq \mathcal{B}$. Several notions of equivalence such as weak equivalence together with (relativized) strong and (relativized) uniform equivalence can be seen as special cases of $\langle \mathcal{H}, \mathcal{B} \rangle$ -equivalence by varying the sets $\mathcal{H}$ and $\mathcal{B}$.

4 SMOLETS program modules

We start this section by introducing the syntax and the stable model semantics for an individual SMOLETS program module, and then formalize the conditions for module composition. One of the main results is the *module theorem* showing that module composition is suitably restricted so that compositionality of stable model semantics for SMOLETS programs is achieved. We also introduce an equivalence relation for modules, and propose a general translation-based scheme for introducing syntactical extensions for the module theorem. The scheme is then utilized in the proof of the module theorem. We end this section with a brief comparison between our module architecture and other similar proposals.

4.1 Syntax and semantics of an `SMODELS` program module

We define a *logic program module* similarly to Gaifman and Shapiro (1989), but consider the case of `SMODELS` programs instead of positive normal logic programs covered in (Gaifman and Shapiro 1989). An analogous module system in the context of *disjunctive logic programs* is presented in (Janhunen et al. 2007).

Definition 4.1 An `SMODELS` program module $\mathbb{P}$ is a quadruple $\langle R, I, O, H \rangle$ where

1. R is a finite set of basic constraint rules;
2. I , O , and H are pairwise disjoint sets of input, output, and hidden atoms;
3. $\text{At}(R) \subseteq \text{At}(\mathbb{P})$ which is defined by $\text{At}(\mathbb{P}) = I \cup O \cup H$; and
4. $\text{Head}(R) \cap I = \emptyset$.

The atoms in $\text{At}_v(\mathbb{P}) = I \cup O$ are considered to be *visible* and hence accessible to other modules conjoined with $\mathbb{P}$; either to produce input for $\mathbb{P}$ or to utilize the output of $\mathbb{P}$. We use notations $\text{At}_i(\mathbb{P})$ and $\text{At}_o(\mathbb{P})$ for referring to the *input signature* I and the *output signature* O , respectively. The *hidden* atoms in $\text{At}_h(\mathbb{P}) = H = \text{At}(\mathbb{P}) \setminus \text{At}_v(\mathbb{P})$ are used to formalize some auxiliary concepts of $\mathbb{P}$ which may not be sensible for other modules but may save space substantially. The use of hidden atoms may yield exponential savings in space, see (Janhunen and Oikarinen 2007, Example 4.5), for instance. The condition $\text{Head}(R) \cap I = \emptyset$ ensures that a module may not interfere with its own input by defining input atoms of I in terms of its rules. Thus input atoms are only allowed to appear as conditions in rule bodies.

Example 4.2 Consider the Hamiltonian cycle problem for directed graphs, that is, whether there is a cycle in the graph such that each node is visited exactly once returning to the starting node.

Let n denote the number of nodes in the graph and let $\text{arc}(x, y)$ denote that there is a directed edge from node x to node y in the graph.

Module $\mathbb{H}^n = \langle R, I, O, \{c, d\} \rangle$ selects the edges to be taken into a cycle by insisting that each node must have exactly one incoming and exactly one outgoing edge. The input signature of $\mathbb{H}^n$ is a graph represented as a set of edges: $I = \{\text{arc}(x, y) \mid 1 \leq x, y \leq n\}$. The output signature of $\mathbb{H}^n$ represents which edges get selected into a candidate for a Hamiltonian cycle: $O = \{\text{hc}(x, y) \mid 1 \leq x, y \leq n\}$. The set R contains rules

$$\{\text{hc}(x, y)\} \leftarrow \text{arc}(x, y) \quad (8)$$

$$c \leftarrow 2 \leq \{\text{hc}(x, 1), \dots, \text{hc}(x, n)\} \quad (9)$$

$$c \leftarrow \sim \text{hc}(x, 1), \dots, \sim \text{hc}(x, n) \quad (10)$$

$$c \leftarrow 2 \leq \{\text{hc}(1, x), \dots, \text{hc}(n, x)\} \text{ and } \quad (11)$$

$$c \leftarrow \sim \text{hc}(1, x), \dots, \sim \text{hc}(n, x) \quad (12)$$

for each $1 \leq x, y \leq n$; and a rule $d \leftarrow \sim d, c$ which enforces c to be false in every stable model. The rules in (8) encode the selection of edges taken in the cycle. The

rules in (9) and (10) are used to guarantee that each node has exactly one outgoing edge, and the rules in (11) and (12) give the respective condition concerning incoming edges.

We also need to check that each node is reachable from the first node along the edges in the cycle. For this, we introduce module $\mathbb{R}^n = \langle R', I', O', \{e\} \rangle$. The input signature of $\mathbb{R}^n$ is $I' = O$, and the output signature is $O' = \{\text{reached}(x) \mid 1 \leq x \leq n\}$, where $\text{reached}(x)$ tells that node x is reachable from the first node. The set R' contains rules

$$\begin{aligned} \text{reached}(y) &\leftarrow \text{hc}(1, y) \\ \text{reached}(y) &\leftarrow \text{reached}(x), \text{hc}(x, y) \\ e &\leftarrow \sim e, \sim \text{reached}(y) \end{aligned}$$

for each $2 \leq x \leq n$ and $1 \leq y \leq n$. ■

To generalize the stable model semantics to cover modules as well, we must explicate the semantical role of input atoms. To this end, we will follow an approach⁴ from (Janhunen et al. 2007) and take input atoms into account in the definition of the reduct adopted from (Janhunen and Oikarinen 2007). It should be stressed that *all negative literals* and *literals involving input atoms* get evaluated in the reduction. Moreover, our definitions become equivalent with those proposed for normal programs (Gelfond and Lifschitz 1988) and SMOELS programs (Janhunen and Oikarinen 2007) if an empty input signature $I = \emptyset$ is additionally assumed. Using the same idea, a conventional SMOELS program, that is, a set of basic constraint rules R , can be viewed as a module $\langle R, \emptyset, \text{At}(R), \emptyset \rangle$ without any input atoms and all atoms visible.

Definition 4.3 *Given a module $\mathbb{P} = \langle R, I, O, H \rangle$, the reduct of R with respect to an interpretation $M \subseteq \text{At}(\mathbb{P})$ and input signature I , denoted by $R^{M,I}$, contains*

1. *a rule $a \leftarrow (B \setminus I)$ if and only if there is a choice rule $\{A\} \leftarrow B, \sim C$ in R such that $a \in A \cap M$, $B \cap I \subseteq M$, and $M \cap C = \emptyset$; and*
2. *a rule $a \leftarrow w' \leq \{B \setminus I = W_{B \setminus I}\}$ if and only if there is a weight rule $a \leftarrow w \leq \{B = W_B, \sim C = W_C\}$ in R , and*

$$w' = \max(0, w - \sum_{b \in B \cap I \cap M} w_b - \sum_{c \in C \setminus M} w_c).$$

As all occurrences of atoms in the input signature and all negative occurrences of atoms are evaluated, the generalized reduct $R^{M,I}$ is a positive program in the sense of (Janhunen and Oikarinen 2007) and thus it has a unique least model $\text{LM}(R^{M,I}) \subseteq \text{At}(R) \setminus I$.

⁴ There are alternative ways to handle input atoms. One possibility is to combine a module with a set of facts (or a database) over its input signature (Oikarinen and Janhunen 2006; Oikarinen 2007). Yet another approach is to interpret input atoms as *fixed atoms* in the sense of parallel circumscription (Lifschitz 1985).

Definition 4.4 *An interpretation $M \subseteq \text{At}(\mathbb{P})$ is a stable model of an SMOELS program module $\mathbb{P} = \langle R, I, O, H \rangle$, denoted by $M \in \text{SM}(\mathbb{P})$, if and only if $M \setminus I = \text{LM}(R^{M,I})$.*

If one is interested in computing stable models of a module with respect to a certain input interpretation, it is easier to use an alternative definition of stable semantics for modules (Oikarinen and Janhunen 2006), where an actual input is seen as a set of facts (or a database) to be combined with the module.

Definition 4.5 *Given an SMOELS program module $\mathbb{P} = \langle R, I, O, H \rangle$ and a set of atoms $A \subseteq I$, the instantiation of $\mathbb{P}$ with an actual input A is*

$$\mathbb{P}(A) = \langle R \cup \{a. \mid a \in A\}, \emptyset, I \cup O, H \rangle.$$

The module $\mathbb{P}(A)$ is essentially an SMOELS program with $I \cup O$ as the set of visible atoms. Thus the stable model semantics of SMOELS programs in Definition 3.3 directly generalizes for an instantiated module.

Definition 4.6 *An interpretation $M \subseteq \text{At}(\mathbb{P})$ is a stable model of an SMOELS program module $\mathbb{P} = \langle R, I, O, H \rangle$ if and only if $M = \text{LM}(R^M \cup \{a. \mid a \in M \cap I\})$.*

It is worth emphasizing that Definitions 4.4 and 4.6 result in exactly the same semantics for SMOELS program modules.

Example 4.7 *Recall module $\mathbb{H}^n$ from Example 4.2. We consider the stable models of $\mathbb{H}^n$ for $n = 2$ to see that the rules in $\mathbb{H}^n$ do not alone guarantee that each node is reachable along the edges taken in the cycle candidate. Consider $M = \{\text{arc}(1, 1), \text{arc}(2, 2), \text{hc}(1, 1), \text{hc}(2, 2)\}$. The reduct $R^{M,I}$ contains facts $\text{hc}(1, 1)$ and $\text{hc}(2, 2)$; and rules $c \leftarrow 2 \leq \{\text{hc}(1, 1), \text{hc}(1, 2)\}$, $c \leftarrow 2 \leq \{\text{hc}(2, 1), \text{hc}(2, 2)\}$, $c \leftarrow 2 \leq \{\text{hc}(1, 1), \text{hc}(2, 1)\}$, and $c \leftarrow 2 \leq \{\text{hc}(1, 2), \text{hc}(2, 2)\}$; and finally the rule $d \leftarrow c$. Now $M \in \text{SM}(\mathbb{H}^n)$ since $M = \text{LM}(R^{M,I})$. However, M does not correspond to a graph with a Hamiltonian cycle, as node 2 is not reachable from node 1. ■*

4.2 Composing programs from modules

The stable model semantics (Gelfond and Lifschitz 1988) does not lend itself directly for program composition. The problem is that in general, stable models associated with modules do not determine stable models assigned to their *composition*.

Gaifman and Shapiro (1989) cover positive normal programs under logical consequences. For their purposes, it is sufficient to assume that whenever two modules $\mathbb{P}_1$ and $\mathbb{P}_2$ are put together, their output signatures have to be disjoint and they have to *respect each other's hidden atoms*, that is, $\text{At}_h(\mathbb{P}_1) \cap \text{At}(\mathbb{P}_2) = \emptyset$ and $\text{At}_h(\mathbb{P}_2) \cap \text{At}(\mathbb{P}_1) = \emptyset$.

Definition 4.8 *Given SMOELS program modules $\mathbb{P}_1 = \langle R_1, I_1, O_1, H_1 \rangle$ and $\mathbb{P}_2 = \langle R_2, I_2, O_2, H_2 \rangle$, their composition is*

$$\mathbb{P}_1 \oplus \mathbb{P}_2 = \langle R_1 \cup R_2, (I_1 \setminus O_2) \cup (I_2 \setminus O_1), O_1 \cup O_2, H_1 \cup H_2 \rangle$$

if $\text{At}_o(\mathbb{P}_1) \cap \text{At}_o(\mathbb{P}_2) = \emptyset$ and $\mathbb{P}_1$ and $\mathbb{P}_2$ respect each other's hidden atoms.

The following example shows that the conditions given for $\oplus$ are not enough to guarantee compositionality in the case of stable models and further restrictions on program composition become necessary.

Example 4.9 Consider normal logic program modules $\mathbb{P}_1 = \langle \{a \leftarrow b.\}, \{b\}, \{a\}, \emptyset \rangle$ and $\mathbb{P}_2 = \langle \{b \leftarrow a.\}, \{a\}, \{b\}, \emptyset \rangle$ both of which have stable models $\emptyset$ and $\{a, b\}$ by symmetry. The composition of $\mathbb{P}_1$ and $\mathbb{P}_2$ is $\mathbb{P}_1 \oplus \mathbb{P}_2 = \langle \{a \leftarrow b. b \leftarrow a.\}, \emptyset, \{a, b\}, \emptyset \rangle$ and $\text{SM}(\mathbb{P}_1 \oplus \mathbb{P}_2) = \{\emptyset\}$, that is, $\{a, b\}$ is not a stable model of $\mathbb{P}_1 \oplus \mathbb{P}_2$. ■

We define the positive dependency graph of an SMOLETS program module $\mathbb{P} = \langle R, I, O, H \rangle$ as $\text{Dep}^+(\mathbb{P}) = \text{Dep}^+(R)$. Given that $\mathbb{P}_1 \oplus \mathbb{P}_2$ is defined, we say that $\mathbb{P}_1$ and $\mathbb{P}_2$ are *mutually dependent* if and only if $\text{Dep}^+(\mathbb{P}_1 \oplus \mathbb{P}_2)$ has an SCC S such that $S \cap \text{At}_o(\mathbb{P}_1) \neq \emptyset$ and $S \cap \text{At}_o(\mathbb{P}_2) \neq \emptyset$, that is, S is *shared by* $\mathbb{P}_1$ and $\mathbb{P}_2$.

Definition 4.10 The join $\mathbb{P}_1 \sqcup \mathbb{P}_2$ of two SMOLETS program modules $\mathbb{P}_1$ and $\mathbb{P}_2$ is $\mathbb{P}_1 \oplus \mathbb{P}_2$, provided $\mathbb{P}_1 \oplus \mathbb{P}_2$ is defined and $\mathbb{P}_1$ and $\mathbb{P}_2$ are not mutually dependent.

Example 4.11 Consider modules $\mathbb{H}^n$ and $\mathbb{R}^n$ from Example 4.2. Since $\mathbb{H}^n$ and $\mathbb{R}^n$ respect each other's hidden atoms and are not mutually dependent, their join $\mathbb{H}^n \sqcup \mathbb{R}^n = \langle R \cup R', I, O \cup O', \{c, d, e\} \rangle$ is defined. ■

The conditions in Definition 4.10 impose no restrictions on positive dependencies *inside* modules or on *negative* dependencies in general. It is straightforward to show that $\sqcup$ has the following properties:

- (i) Identity: $\mathbb{P} \sqcup \langle \emptyset, \emptyset, \emptyset, \emptyset \rangle = \langle \emptyset, \emptyset, \emptyset, \emptyset \rangle \sqcup \mathbb{P} = \mathbb{P}$ for all modules $\mathbb{P}$.
- (ii) Commutativity: $\mathbb{P}_1 \sqcup \mathbb{P}_2 = \mathbb{P}_2 \sqcup \mathbb{P}_1$ for all modules $\mathbb{P}_1$ and $\mathbb{P}_2$ such that $\mathbb{P}_1 \sqcup \mathbb{P}_2$ is defined.
- (iii) Associativity: $(\mathbb{P}_1 \sqcup \mathbb{P}_2) \sqcup \mathbb{P}_3 = \mathbb{P}_1 \sqcup (\mathbb{P}_2 \sqcup \mathbb{P}_3)$ for all modules $\mathbb{P}_1, \mathbb{P}_2$ and $\mathbb{P}_3$ such that all pairwise joins are defined.

The equality “=” used above denotes syntactical equality. Also note that $\mathbb{P} \sqcup \mathbb{P}$ is usually undefined, which is a difference with respect to $\cup$ for which it holds that $P \cup P = P$ for all programs P . Furthermore, considering the join $\mathbb{P}_1 \sqcup \mathbb{P}_2$, since each atom is defined in exactly one module, the sets of rules in $\mathbb{P}_1$ and $\mathbb{P}_2$ are distinct, that is, $R_1 \cap R_2 = \emptyset$, and also, $\text{At}(\mathbb{P}_1 \sqcup \mathbb{P}_2) = \text{At}(\mathbb{P}_1) \cup \text{At}(\mathbb{P}_2)$, $\text{At}_v(\mathbb{P}_1 \sqcup \mathbb{P}_2) = \text{At}_v(\mathbb{P}_1) \cup \text{At}_v(\mathbb{P}_2)$, and $\text{At}_h(\mathbb{P}_1 \sqcup \mathbb{P}_2) = \text{At}_h(\mathbb{P}_1) \cup \text{At}_h(\mathbb{P}_2)$.

Having the semantics of an individual SMOLETS program module now defined, we may characterize the properties of the semantics under program composition using the notion of *compatibility*.

Definition 4.12 Given SMOLETS program modules $\mathbb{P}_1$ and $\mathbb{P}_2$ such that $\mathbb{P}_1 \oplus \mathbb{P}_2$ is defined, we say that interpretations $M_1 \subseteq \text{At}(\mathbb{P}_1)$ and $M_2 \subseteq \text{At}(\mathbb{P}_2)$ are *compatible* if and only if $M_1 \cap \text{At}_v(\mathbb{P}_2) = M_2 \cap \text{At}_v(\mathbb{P}_1)$.

We use *natural join* $\bowtie$ to combine compatible interpretations.

Definition 4.13 Given *SMODELS* program modules $\mathbb{P}_1$ and $\mathbb{P}_2$ and sets of interpretations $A_1 \subseteq \mathbf{2}^{\text{At}(\mathbb{P}_1)}$ and $A_2 \subseteq \mathbf{2}^{\text{At}(\mathbb{P}_2)}$, the natural join of A_1 and A_2 , denoted by $A_1 \bowtie A_2$, is

$$\{M_1 \cup M_2 \mid M_1 \in A_1, M_2 \in A_2 \text{ such that } M_1 \text{ and } M_2 \text{ are compatible}\}.$$

The stable model semantics is compositional for $\sqcup$, that is, if a program (module) consists of several submodules, its stable models are locally stable for the respective submodules; and on the other hand, local stability implies global stability for compatible stable models of the submodules.

Theorem 4.14 (Module theorem (Oikarinen 2007)) If $\mathbb{P}_1$ and $\mathbb{P}_2$ are *SMODELS* program modules such that $\mathbb{P}_1 \sqcup \mathbb{P}_2$ is defined, then

$$\text{SM}(\mathbb{P}_1 \sqcup \mathbb{P}_2) = \text{SM}(\mathbb{P}_1) \bowtie \text{SM}(\mathbb{P}_2).$$

Instead of proving Theorem 4.14 directly from scratch we will propose a *general translation-based scheme* for introducing syntactical extensions for the module theorem. For this we need to define a concept of *modular equivalence* first, and thus the proof of Theorem 4.14 is deferred until Section 4.4.

It is worth noting that classical propositional theories have an analogous property obtained by substituting $\cup$ for $\sqcup$ and replacing stable models by classical models in Theorem 4.14, that is, for any *SMODELS* programs P_1 and P_2 , $\text{CM}(P_1 \cup P_2) = \text{CM}(P_1) \bowtie \text{CM}(P_2)$, where $\text{CM}(P) = \{M \subseteq \text{At}(P) \mid M \models P\}$.

Example 4.15 Recall modules $\mathbb{H}^n$ and $\mathbb{R}^n$ in Example 4.2. In Example 4.7 we showed that $M = \{\text{arc}(1, 1), \text{arc}(2, 2), \text{hc}(1, 1), \text{hc}(2, 2)\}$ is a stable model of $\mathbb{H}^2$. Now module $\mathbb{R}^2$ has six stable models, but none of them is compatible with M . Thus by Theorem 4.14 there is no stable model N for $\mathbb{H}^2 \sqcup \mathbb{R}^2$ such that $N \cap \text{At}(\mathbb{H}^2) = M$.

The join $\mathbb{H}^n \sqcup \mathbb{R}^n$ can be used to find any graph of n nodes which has a Hamiltonian cycle. For instance $\mathbb{H}^2 \sqcup \mathbb{R}^2$ has four stable models:

$$\begin{aligned} &\{\text{arc}(1, 2), \text{arc}(2, 1), \text{hc}(1, 2), \text{hc}(2, 1), \text{reached}(1), \text{reached}(2)\} \\ &\{\text{arc}(1, 1), \text{arc}(1, 2), \text{arc}(2, 1), \text{hc}(1, 2), \text{hc}(2, 1), \text{reached}(1), \text{reached}(2)\} \\ &\{\text{arc}(1, 2), \text{arc}(2, 1), \text{arc}(2, 2), \text{hc}(1, 2), \text{hc}(2, 1), \text{reached}(1), \text{reached}(2)\} \\ &\{\text{arc}(1, 1), \text{arc}(1, 2), \text{arc}(2, 1), \text{arc}(2, 2), \text{hc}(1, 2), \text{hc}(2, 1), \text{reached}(1), \text{reached}(2)\}. \end{aligned}$$

These models represent the four possible graphs of two nodes having a Hamiltonian cycle. ■

Theorem 4.14 straightforwardly generalizes for modules consisting of several submodules. Consider a collection of *SMODELS* program modules $\mathbb{P}_1, \dots, \mathbb{P}_n$ such that the join $\mathbb{P}_1 \sqcup \dots \sqcup \mathbb{P}_n$ is defined (recall that $\sqcup$ is associative). We say that a collection of interpretations $\{M_1, \dots, M_n\}$ for modules $\mathbb{P}_1, \dots, \mathbb{P}_n$, respectively, is *compatible*, if and only if M_i and M_j are pairwise compatible for all $1 \leq i, j \leq n$. The natural join generalizes for a collection of modules as

$$A_1 \bowtie \dots \bowtie A_n = \{M_1 \cup \dots \cup M_n \mid M_i \in A_i \text{ and } \{M_1, \dots, M_n\} \text{ is compatible}\},$$

where $A_1 \subseteq \mathbf{2}^{\text{At}(\mathbb{P}_1)}, \dots, A_n \subseteq \mathbf{2}^{\text{At}(\mathbb{P}_n)}$.

Corollary 4.16 *For a collection of SMOLETS program modules $\mathbb{P}_1, \dots, \mathbb{P}_n$ such that the join $\mathbb{P}_1 \sqcup \dots \sqcup \mathbb{P}_n$ is defined, it holds that*

$$\text{SM}(\mathbb{P}_1 \sqcup \dots \sqcup \mathbb{P}_n) = \text{SM}(\mathbb{P}_1) \bowtie \dots \bowtie \text{SM}(\mathbb{P}_n).$$

Although Corollary 4.16 enables the computation of stable models on a module-by-module basis, it leaves us the task of excluding mutually incompatible combinations of stable models. It should be noted that applying the module theorem in a naive way by first computing stable models for each submodule and finding then the compatible pairs afterwards, might not be preferable.

Example 4.17 *Consider SMOLETS program modules*

$$\begin{aligned} \mathbb{P}_1 &= \langle \{a \leftarrow \sim b.\}, \{b\}, \{a\}, \emptyset \rangle, \\ \mathbb{P}_2 &= \langle \{b \leftarrow \sim c.\}, \{c\}, \{b\}, \emptyset \rangle, \text{ and} \\ \mathbb{P}_3 &= \langle \{c \leftarrow \sim a.\}, \{a\}, \{c\}, \emptyset \rangle, \end{aligned}$$

and their join $\mathbb{P} = \mathbb{P}_1 \sqcup \mathbb{P}_2 \sqcup \mathbb{P}_3 = \langle \{a \leftarrow \sim b. b \leftarrow \sim c. c \leftarrow \sim a.\}, \emptyset, \{a, b, c\}, \emptyset \rangle$. We have $\text{SM}(\mathbb{P}_1) = \{\{a\}, \{b\}\}$, $\text{SM}(\mathbb{P}_2) = \{\{b\}, \{c\}\}$, and $\text{SM}(\mathbb{P}_3) = \{\{a\}, \{c\}\}$. To apply Corollary 4.16 for finding $\text{SM}(\mathbb{P})$, a naive approach is to compute all stable models of all the modules and try to find a compatible triple of stable models M_1 , M_2 , and M_3 for $\mathbb{P}_1$, $\mathbb{P}_2$, and $\mathbb{P}_3$, respectively.

- Now $\{a\} \in \text{SM}(\mathbb{P}_1)$ and $\{c\} \in \text{SM}(\mathbb{P}_2)$ are compatible, since $\{a\} \cap \text{At}_v(\mathbb{P}_2) = \emptyset = \{c\} \cap \text{At}_v(\mathbb{P}_1)$. However, $\{a\} \in \text{SM}(\mathbb{P}_3)$ is not compatible with $\{c\} \in \text{SM}(\mathbb{P}_2)$, since $\{c\} \cap \text{At}_v(\mathbb{P}_3) = \{c\} \neq \emptyset = \{a\} \cap \text{At}_v(\mathbb{P}_2)$. On the other hand, $\{c\} \in \text{SM}(\mathbb{P}_3)$ is not compatible with $\{a\} \in \text{SM}(\mathbb{P}_1)$, since $\{a\} \cap \text{At}_v(\mathbb{P}_3) = \{a\} \neq \emptyset = \{c\} \cap \text{At}_v(\mathbb{P}_1)$.
- Also $\{b\} \in \text{SM}(\mathbb{P}_1)$ and $\{b\} \in \text{SM}(\mathbb{P}_2)$ are compatible, but $\{b\} \in \text{SM}(\mathbb{P}_1)$ is incompatible with $\{a\} \in \text{SM}(\mathbb{P}_3)$. Nor is $\{b\} \in \text{SM}(\mathbb{P}_2)$ compatible with $\{c\} \in \text{SM}(\mathbb{P}_3)$.

Thus there are no $M_1 \in \text{SM}(\mathbb{P}_1)$, $M_2 \in \text{SM}(\mathbb{P}_2)$, and $M_3 \in \text{SM}(\mathbb{P}_3)$ such that $\{M_1, M_2, M_3\}$ is compatible, which is natural as $\text{SM}(\mathbb{P}) = \emptyset$. ■

It is not necessary to test all combinations of stable models to see whether we have a compatible triple. Instead, we use the alternative definition of stable models (Definition 4.6) based on instantiating the module with respect to an input interpretation, and apply the module theorem similarly to the splitting-set theorem. One should notice that the set of rules in $\mathbb{P}$ presented in Example 4.17 has no non-trivial splitting sets, and thus the splitting-set theorem is not applicable (in a non-trivial way) in this case.

Example 4.18 *Consider SMOLETS program modules $\mathbb{P}_1$, $\mathbb{P}_2$, and $\mathbb{P}_3$ from Example 4.17. Now, $\mathbb{P}_1$ has two stable models $M_1 = \{a\}$ and $M_2 = \{b\}$.*

- The set $M_1 \cap \text{At}_i(\mathbb{P}_3) = \{a\} = A_1$ can be seen as an input interpretation for $\mathbb{P}_3$. Module $\mathbb{P}_3$ instantiated with A_1 has one stable model: $\text{SM}(\mathbb{P}_3(A_1)) = \{\{a\}\}$. Furthermore, we can use $A_2 = \{a\} \cap \text{At}_i(\mathbb{P}_2) = \emptyset$ to instantiate $\mathbb{P}_2$: $\text{SM}(\mathbb{P}_2(A_2)) =$

$\{\{b\}\}$. However, $\{b\}$ is not compatible with M_1 , and thus there is no way to find a compatible collection of stable models for the modules starting from M_1 .

- We instantiate $\mathbb{P}_3$ with $M_2 \cap \text{At}_i(\mathbb{P}_3) = \emptyset = A_3$ and get $\text{SM}(\mathbb{P}_3(A_3)) = \{\{c\}\}$. Continuing with $\{c\} \cap \text{At}_i(\mathbb{P}_2) = \{c\} = A_4$, we get $\text{SM}(\mathbb{P}_2(A_4)) = \{\{c\}\}$. Again, we notice that $\{c\}$ is not compatible with M_2 , and thus it is not possible to find a compatible triple of stable models starting from M_2 either.

Thus we can conclude $\text{SM}(\mathbb{P}) = \emptyset$. ■

4.3 Equivalence relations for modules

The notion of *visible equivalence* (Janhunen 2006) was introduced in order to neglect hidden atoms when logic programs or other theories of interest are compared on the basis of their models. The compositionality property from Theorem 4.14 enables us to bring the same idea to the level of program modules—giving rise to *modular equivalence* of logic programs. Visible and modular equivalence are formulated for SMOELS program modules as follows.

Definition 4.19 For two SMOELS program modules $\mathbb{P}$ and $\mathbb{Q}$,

- $\mathbb{P} \equiv_v \mathbb{Q}$ if and only if $\text{At}_v(\mathbb{P}) = \text{At}_v(\mathbb{Q})$ and there is a bijection $f : \text{SM}(\mathbb{P}) \rightarrow \text{SM}(\mathbb{Q})$ such that for all $M \in \text{SM}(\mathbb{P})$,

$$M \cap \text{At}_v(\mathbb{P}) = f(M) \cap \text{At}_v(\mathbb{Q}); \text{ and}$$

- $\mathbb{P} \equiv_m \mathbb{Q}$ if and only if $\text{At}_i(\mathbb{P}) = \text{At}_i(\mathbb{Q})$ and $\mathbb{P} \equiv_v \mathbb{Q}$.

We note that the condition $\text{At}_v(\mathbb{P}) = \text{At}_v(\mathbb{Q})$ insisted on the definition of $\equiv_v$, implies $\text{At}_o(\mathbb{P}) = \text{At}_o(\mathbb{Q})$ in the presence of $\text{At}_i(\mathbb{P}) = \text{At}_i(\mathbb{Q})$ as required by the relation $\equiv_m$. Moreover, these relations coincide for completely specified SMOELS programs, that is modules $\mathbb{P}$ with $\text{At}_i(\mathbb{P}) = \emptyset$.

Modular equivalence lends itself for program substitutions in analogy to *strong equivalence* (Lifschitz et al. 2001), that is, the relation $\equiv_m$ is a proper *congruence* for the join operator $\sqcup$.

Theorem 4.20 (Congruence) Let $\mathbb{P}, \mathbb{Q}$ and $\mathbb{R}$ be SMOELS program modules such that $\mathbb{P} \sqcup \mathbb{R}$ and $\mathbb{Q} \sqcup \mathbb{R}$ are defined. If $\mathbb{P} \equiv_m \mathbb{Q}$, then $\mathbb{P} \sqcup \mathbb{R} \equiv_m \mathbb{Q} \sqcup \mathbb{R}$.

The proof of Theorem 4.20 is given in Appendix A. The following examples illustrate the use of modular equivalence in practice.

Example 4.21 Recall programs $P = \{a.\}$ and $Q = \{a \leftarrow \sim b. \ a \leftarrow b.\}$ from Example 3.13. We can define modules based on them: $\mathbb{P} = \langle P, \{b\}, \{a\}, \emptyset \rangle$ and $\mathbb{Q} = \langle Q, \{b\}, \{a\}, \emptyset \rangle$. Now it is impossible to define a module $\mathbb{R}$ based on $R = \{b \leftarrow a.\}$ in a way that $\mathbb{Q} \sqcup \mathbb{R}$ would be defined. Moreover, it holds that $\mathbb{P} \equiv_m \mathbb{Q}$. ■

Example 4.22 Module $\mathbb{H}R^n = \langle R'', I'', O'', \{f\} \rangle$ is based on an alternative encoding for Hamiltonian cycle problem given in (Simons et al. 2002). In contrast to the

encoding described in Example 4.2, this encoding does not allow us to separate the selection of the edges to the cycle and the checking of reached vertices into separate modules as their definitions are mutually dependent. The input signature of $\mathbb{H}\mathbb{R}^n$ is the same as for $\mathbb{H}^n$, that is, $I'' = I = \{\text{arc}(x, y) \mid 1 \leq x, y \leq n\}$. The output signature of $\mathbb{H}\mathbb{R}^n$ is the output signature of $\mathbb{H}^n \sqcup \mathbb{R}^n$, that is,

$$O'' = O \cup O' = \{\text{hc}(x, y) \mid 1 \leq x, y \leq n\} \cup \{\text{reached}(x) \mid 1 \leq x \leq n\}.$$

The set R'' contains rules

$$\begin{aligned} \{\text{hc}(1, x)\} &\leftarrow \text{arc}(1, x) \\ \{\text{hc}(x, y)\} &\leftarrow \text{reached}(x), \text{arc}(x, y) \\ \text{reached}(y) &\leftarrow \text{hc}(x, y) \\ f &\leftarrow \sim f, \sim \text{reached}(x) \\ f &\leftarrow \sim f, \text{hc}(x, y), \text{hc}(x, z) \text{ and} \\ f &\leftarrow \sim f, \text{hc}(x, y), \text{hc}(z, y) \end{aligned} \tag{13}$$

for each $1 \leq x, y, z \leq n$ such that $y \neq z$ in (13) and $x \neq z$ in (14).

Now, one may notice that $\mathbb{H}\mathbb{R}^n$ and $\mathbb{H}^n \sqcup \mathbb{R}^n$ have the same input/output interface, and $\text{SM}(\mathbb{H}\mathbb{R}^n) = \text{SM}(\mathbb{H}^n \sqcup \mathbb{R}^n)$ which implies $\mathbb{H}\mathbb{R}^n \equiv_m \mathbb{H}^n \sqcup \mathbb{R}^n$. ■

As regards the relationship between modular equivalence and previously proposed notions of equivalence, we note the following. First, if one considers the *fully visible case*, that is, the restriction $\text{At}_h(\mathbb{P}) = \text{At}_h(\mathbb{Q}) = \emptyset$, modular equivalence can be seen as a special case of A -uniform equivalence for $A = I$. Recall, however, the restriction that input atoms may not appear in the heads of the rules as imposed by module structure. With a further restriction $\text{At}_i(\mathbb{P}) = \text{At}_i(\mathbb{Q}) = \emptyset$, modular equivalence basically coincides with weak equivalence because $\text{At}(\mathbb{P}) = \text{At}(\mathbb{Q})$ can always be satisfied by extending the interface of the module. Setting $\text{At}_i(\mathbb{P}) = \text{At}(\mathbb{P})$ would in principle give us uniform equivalence, but the additional condition $\text{Head}(R) \cap I = \emptyset$ leaves room for the empty module only.

In the general case with hidden atoms, the problem of verifying $\equiv_m$ for SMOLETS program modules can be reduced to verifying $\equiv_v$ for SMOLETS programs. This is achieved by introducing a special module $\mathbb{G}_I$ containing a single choice rule, which acts as a context generator in analogy to (Woltran 2004). We say that two modules $\mathbb{P}$ and $\mathbb{Q}$ are *compatible* if they have the same input/output interface, that is, $\text{At}_i(\mathbb{P}) = \text{At}_i(\mathbb{Q})$ and $\text{At}_o(\mathbb{P}) = \text{At}_o(\mathbb{Q})$.

Lemma 4.23 *Consider compatible SMOLETS program modules $\mathbb{P}$ and $\mathbb{Q}$. Now $\mathbb{P} \equiv_m \mathbb{Q}$ if and only if $\mathbb{P} \sqcup \mathbb{G}_I \equiv_v \mathbb{Q} \sqcup \mathbb{G}_I$ where $I = \text{At}_i(\mathbb{P}) = \text{At}_i(\mathbb{Q})$ and $\mathbb{G}_I = \langle \{\{I\} \leftarrow \}, \emptyset, I, \emptyset \rangle$ generates all possible input interpretations for $\mathbb{P}$ and $\mathbb{Q}$.*

Proof

Notice that $\mathbb{P} \sqcup \mathbb{G}_I$ and $\mathbb{Q} \sqcup \mathbb{G}_I$ are SMOLETS program modules with empty input signatures, and thus they can also be viewed as SMOLETS programs. ($\implies$) Assume $\mathbb{P} \equiv_m \mathbb{Q}$. Since $\mathbb{P} \sqcup \mathbb{G}_I$ and $\mathbb{Q} \sqcup \mathbb{G}_I$ are defined, $\mathbb{P} \sqcup \mathbb{G}_I \equiv_m \mathbb{Q} \sqcup \mathbb{G}_I$ by Theorem

4.20. This implies $\mathbb{P} \sqcup \mathbb{G}_I \equiv_v \mathbb{Q} \sqcup \mathbb{G}_I$. ($\Leftarrow$) Assume $\mathbb{P} \sqcup \mathbb{G}_I \equiv_v \mathbb{Q} \sqcup \mathbb{G}_I$, that is, $\text{At}_v(\mathbb{P}) = \text{At}_v(\mathbb{Q})$ and there is a bijection $f : \text{SM}(\mathbb{P} \sqcup \mathbb{G}_I) \rightarrow \text{SM}(\mathbb{Q} \sqcup \mathbb{G}_I)$ such that for each $M \in \text{SM}(\mathbb{P} \sqcup \mathbb{G}_I)$, $M \cap \text{At}_v(\mathbb{P}) = f(M) \cap \text{At}_v(\mathbb{Q})$. By Theorem 4.14, $\text{SM}(\mathbb{P} \sqcup \mathbb{G}_I) = \text{SM}(\mathbb{P}) \bowtie \text{SM}(\mathbb{G}_I)$ and $\text{SM}(\mathbb{Q} \sqcup \mathbb{G}_I) = \text{SM}(\mathbb{Q}) \bowtie \text{SM}(\mathbb{G}_I)$. Now, $\text{SM}(\mathbb{G}_I) = \mathbf{2}^I$, and thus $\text{SM}(\mathbb{P} \sqcup \mathbb{G}_I) = \text{SM}(\mathbb{P})$ and $\text{SM}(\mathbb{Q} \sqcup \mathbb{G}_I) = \text{SM}(\mathbb{Q})$. This implies $\mathbb{P} \equiv_v \mathbb{Q}$, and furthermore $\mathbb{P} \equiv_m \mathbb{Q}$ since $\mathbb{P}$ and $\mathbb{Q}$ are compatible SMOELS program modules. $\square$

Due to the close relationship of $\equiv_v$ and $\equiv_m$, the respective verification problems have the same computational complexity. As already observed in (Janhunen and Oikarinen 2007), the verification of $\mathbb{P} \equiv_v \mathbb{Q}$ involves a *counting problem* in general and, in particular, if $\text{At}_v(\mathbb{P}) = \text{At}_v(\mathbb{Q}) = \emptyset$. In this special setting $\mathbb{P} \equiv_v \mathbb{Q}$ holds if and only if $|\text{SM}(\mathbb{P})| = |\text{SM}(\mathbb{Q})|$, that is, the numbers of stable models for $\mathbb{P}$ and $\mathbb{Q}$ coincide. A reduction of computational time complexity can be achieved for modules that have *enough visible atoms*, that is, the EVA property. Basically, we say that module $\mathbb{P} = \langle R, I, O, H \rangle$ has enough visible atoms, if and only if R has enough visible atoms with respect to $\text{At}_v(P) = I \cup O$. However, the property of having enough visible atoms can be elegantly stated using modules. We define the *hidden part* of a module $\mathbb{P} = \langle R, I, O, H \rangle$ as $\mathbb{P}_h = \langle R_h, I \cup O, H, \emptyset \rangle$ where R_h contains all rules of R involving atoms of H in their heads. For a choice rule $\{A\} \leftarrow B, \sim C \in R$, we take the projection $\{A \cap H\} \leftarrow B, \sim C$ in R_h .

Definition 4.24 (The EVA property (Janhunen and Oikarinen 2007))

An SMOELS program module $\mathbb{P} = \langle R, I, O, H \rangle$ has enough visible atoms if and only if the hidden part $\mathbb{P}_h = \langle R_h, I \cup O, H, \emptyset \rangle$ has a unique stable model M for each interpretation $N \subseteq \text{At}_v(\mathbb{P}) = I \cup O$ such that $M \cap (I \cup O) = N$.

Verifying the EVA property is **coNP**-hard and in Π_2^P for SMOELS programs (Janhunen and Oikarinen 2007, Proposition 4.14), and thus for SMOELS program modules, too. It is always possible to enforce the EVA property by uncovering sufficiently many hidden atoms: a module $\mathbb{P}$ for which $\text{At}_h(\mathbb{P}) = \emptyset$ has clearly enough visible atoms because $\mathbb{P}_h$ has no rules. It is also important to realize that choice rules involving hidden atoms in their heads most likely break up the EVA property—unless additional constraints are introduced to exclude multiple models created by choices.

Based on the observations we can conclude that verifying the modular equivalence of modules with the EVA property is a **coNP**-complete decision problem. Motivated by the complexity result and by previous proposals for translating various equivalence verification problems into the problem of computing stable models (see (Janhunen and Oikarinen 2002; Turner 2003; Woltran 2004) for instance), we recently introduced a translation-based method for verifying modular equivalence (Oikarinen and Janhunen 2008b). In the following theorem, $\text{EQT}(\cdot, \cdot)$ is the linear translation function mapping two SMOELS program modules into one SMOELS program module presented in (Oikarinen and Janhunen 2008b, Definition 10).

Theorem 4.25 ((Oikarinen and Janhunen 2008b, Theorem 4)) *Let $\mathbb{P}$ and $\mathbb{Q}$ be compatible SMODELS program modules with the EVA property, and $\mathbb{C}$ any SMODELS program module such that $\mathbb{P} \sqcup \mathbb{C}$ and $\mathbb{Q} \sqcup \mathbb{C}$ are defined. Then $\mathbb{P} \sqcup \mathbb{C} \equiv_m \mathbb{Q} \sqcup \mathbb{C}$ if and only if $\text{SM}(\text{EQT}(\mathbb{P}, \mathbb{Q}) \sqcup \mathbb{C}) = \text{SM}(\text{EQT}(\mathbb{Q}, \mathbb{P}) \sqcup \mathbb{C}) = \emptyset$.*

4.4 Proving the module theorem using a general translation-based extension scheme

Let us now proceed to the proof of the module theorem. We describe the overall strategy in this section whereas detailed proofs for the theorems are provided in Appendix A. Instead of proving Theorem 4.14 from scratch, we first show that the theorem holds for normal logic program modules, and then present a general scheme that enables us to derive extensions of the module theorem syntactically in terms of translations.

We start by stating the module theorem for normal logic program modules.

Theorem 4.26 ((Oikarinen and Janhunen 2006)) *If $\mathbb{P}_1$ and $\mathbb{P}_2$ are normal logic program modules such that $\mathbb{P}_1 \sqcup \mathbb{P}_2$ is defined, then*

$$\text{SM}(\mathbb{P}_1 \sqcup \mathbb{P}_2) = \text{SM}(\mathbb{P}_1) \bowtie \text{SM}(\mathbb{P}_2).$$

Proof for Theorem 4.26 is given in Appendix A.

Next definition states the conditions which we require a translation function to have in order to achieve syntactical extensions to the module theorem. Intuitively, the conditions serve the following purposes: first, the translation has to be *strongly faithful*, that is, it preserves the roles of all atoms in the original module; second, it is $\sqcup$ -*preserving*, that is, possible compositions of modules are not limited by the translation; and third, the translation is *modular*.

For convenience, we define an operator $\text{reveal}(\mathbb{P}, A) = \langle R, I, O \cup A, H \setminus A \rangle$ for any program module $\mathbb{P} = \langle R, I, O, H \rangle$ and for any set of atoms $A \subseteq H$. The revealing operator is used to make a set of hidden atoms of a module visible to other modules.

Definition 4.27 *Let $\mathcal{C}_1$ and $\mathcal{C}_2$ be two classes of logic program modules such that $\mathcal{C}_2 \subseteq \mathcal{C}_1$. A translation function $\text{Tr} : \mathcal{C}_1 \rightarrow \mathcal{C}_2$ is strongly faithful, modular and $\sqcup$ -preserving, if the following hold for any program modules $\mathbb{P}, \mathbb{Q} \in \mathcal{C}_1$:*

1. $\text{reveal}(\mathbb{P}, \text{At}_h(\mathbb{P})) \equiv_m \text{reveal}(\text{Tr}(\mathbb{P}), \text{At}_h(\mathbb{P}))$;
2. *if $\mathbb{P} \sqcup \mathbb{Q}$ is defined, then $\text{Tr}(\mathbb{P}) \sqcup \text{Tr}(\mathbb{Q})$ is defined; and*
3. $\text{Tr}(\mathbb{P}) \sqcup \text{Tr}(\mathbb{Q}) = \text{Tr}(\mathbb{P} \sqcup \mathbb{Q})$.

Notice that the condition for strong faithfulness requires $\text{At}_i(\text{Tr}(\mathbb{P})) = \text{At}_i(\mathbb{P})$, $\text{At}_o(\text{Tr}(\mathbb{P})) \cup \text{At}_h(\mathbb{P}) = \text{At}_o(\mathbb{P}) \cup \text{At}_h(\mathbb{P})$, and $\text{At}_h(\mathbb{P}) \subseteq \text{At}_h(\text{Tr}(\mathbb{P}))$ to hold. Moreover, strong faithfulness implies *faithfulness*, that is, $\mathbb{P} \equiv_m \text{Tr}(\mathbb{P})$.

Theorem 4.28 *Let $\mathcal{C}_1$ and $\mathcal{C}_2$ be two classes of logic program modules such that $\mathcal{C}_2 \subseteq \mathcal{C}_1$ and there is a translation function $\text{Tr} : \mathcal{C}_1 \rightarrow \mathcal{C}_2$ that is strongly faithful,*

$\sqsubseteq$ -preserving, and modular as given in Definition 4.27. If the module theorem holds for modules in $\mathcal{C}_2$, then it holds for modules in $\mathcal{C}_1$.

The proof of Theorem 4.28 is provided in Appendix A.

As regards the translation from SMOLELS program modules to NLP modules, it suffices, for example, to take a natural translation similarly to (Simons et al. 2002). Note that the translation presented in Definition 4.29 is in the worst case exponential with respect to the number of rules in the original module. For a more compact translation, see (Ferraris and Lifschitz 2005), for example.

Definition 4.29 *Given an SMOLELS program module $\mathbb{P} = \langle R, I, O, H \rangle$, its translation into a normal logic program module is $\text{Tr}_{\text{NLP}}(\mathbb{P}) = \langle R', I, O, H \cup H' \rangle$, where R' contains the following rules:*

- for each choice rule $\{A\} \leftarrow B, \sim C \in R$ the set of rules

$$\{a \leftarrow B, \sim C, \sim \bar{a}. \quad \bar{a} \leftarrow \sim a \mid a \in A\};$$

- for each weight rule $a \leftarrow w \leq \{B = W_B, \sim C = W_C\} \in R$ the set of rules

$$\{a \leftarrow B', \sim C' \mid B' \subseteq B, C' \subseteq C \text{ and } w \leq \sum_{b \in B'} w_b + \sum_{c \in C'} w_c\},$$

where each $\bar{a}$ is a new atom not appearing in $\text{At}(\mathbb{P})$ and $H' = \{\bar{a} \mid a \in \text{Choices}(R)\}$.

Theorem 4.30 *The translation Tr_{NLP} from SMOLELS program modules to normal logic program modules given in Definition 4.29 is strongly faithful, $\sqsubseteq$ -preserving, and modular.*

The proof of Theorem 4.30 is given in Appendix A.

The module theorem now directly follows from Theorems 4.26, 4.28, and 4.30.

Proof of Theorem 4.14

By Theorem 4.26 we know that the module theorem holds for normal logic program modules. Theorem 4.28 shows that Definition 4.27 gives the conditions under which Theorem 4.26 can be directly generalized for a larger class of logic program modules. By Theorem 4.30 we know that the translation Tr_{NLP} from SMOLELS program modules to NLP modules introduced in Definition 4.29 satisfies the conditions given in Definition 4.27, and therefore SMOLELS program modules are covered by the module theorem. $\square$

4.5 Comparison with earlier approaches

Our module system resembles the module system proposed in (Gaifman and Shapiro 1989). However, to make our system compatible with the stable model semantics we need to introduce a further restriction of mutual dependence, that is, we need to deny positive recursion between modules. Also other propositions involve similar conditions for module composition. For example, Brogi et al. (1994) employ visibility conditions that correspond to respecting hidden atoms. However, their approach

covers only positive programs under the least model semantics. Maher (1993) forbids all recursion between modules and considers Przymusiński's *perfect models* (Przymusiński 1988) rather than stable models. Etalle and Gabbrielli (1996) restrict the composition of *constraint logic program* (Jaffar and Maher 1994) modules with a condition that is close to ours: $\text{At}(P) \cap \text{At}(Q) \subseteq \text{At}_v(P) \cap \text{At}_v(Q)$ but no distinction between input and output is made, for example, $\text{At}_o(P) \cap \text{At}_o(Q) \neq \emptyset$ is allowed according to their definitions.

Approaches to modularity within ASP typically do not allow any recursion (negative or positive) between modules (Eiter et al. 1997; Tari et al. 2005; Lifschitz and Turner 1994; Gelfond and Gabaldon 1999). Theorem 4.14, the module theorem, is strictly stronger than the splitting-set theorem (Lifschitz and Turner 1994) for normal logic programs, and the general case allows us to generalize the splitting-set theorem for SMOELS programs. Consider first the case of normal logic programs. A *splitting* of a program can be used as a basis for a module structure. If U is a splitting set for a normal logic program P , then we can define

$$P = \mathbb{B} \sqcup \mathbb{T} = \langle \text{b}_U(P), \emptyset, U, \emptyset \rangle \sqcup \langle \text{t}_U(P), U, \text{At}(P) \setminus U, \emptyset \rangle.$$

It follows directly from Theorems 3.6 and 4.14 that $M_1 \in \text{SM}(\mathbb{B})$ and $M_2 \in \text{SM}(\mathbb{T})$ are compatible if and only if $\langle M_1, M_2 \setminus U \rangle$ is a solution for P with respect to U .

Example 4.31 Consider a normal logic program $P = \{a \leftarrow \sim b. \ b \leftarrow \sim a. \ c \leftarrow a.\}$. The set $U = \{a, b\}$ is a splitting set for P , and therefore the splitting set-theorem (Theorem 3.6) can be applied: $\text{b}_U(P) = \{a \leftarrow \sim b. \ b \leftarrow \sim a.\}$ and $\text{t}_U(P) = \{c \leftarrow a.\}$. Now $M_1 = \{a\}$ and $M_2 = \{b\}$ are the stable models of $\text{b}_U(P)$, and we can evaluate the top with respect to M_1 and M_2 , resulting in solutions $\langle M_1, \{c\} \rangle$ and $\langle M_2, \emptyset \rangle$, respectively. On the other hand, P can be seen as join of modules $\mathbb{P}_1 = \langle \text{b}_U(P), \emptyset, U, \emptyset \rangle$ and $\mathbb{P}_2 = \langle \text{t}_U(P), U, \{c\}, \emptyset \rangle$. Now, we have $\text{SM}(\mathbb{P}_1) = \{M_1, M_2\}$ and $\text{SM}(\mathbb{P}_2) = \{\emptyset, \{b\}, \{a, c\}, \{a, b, c\}\}$. Out of eight possible pairs only $\langle M_1, \{a, c\} \rangle$ and $\langle M_2, \{b\} \rangle$ are compatible.

However, it is possible to apply Theorem 4.14 similarly to the splitting-set theorem, that is, we only need to compute the stable models of $\mathbb{P}_2$ compatible with the stable models of $\mathbb{P}_1$. Notice that when the splitting-set theorem is applicable, the stable models of $\mathbb{P}_1$ fully define the possible input interpretations for $\mathbb{P}_2$. This leaves us with stable models $\{a, c\}$ and $\{b\}$ for the composition. ■

On the other hand, consider the module $\mathbb{P}_1 = \langle \text{b}_U(P), \emptyset, U, \emptyset \rangle$ in the above example. There are no non-trivial splitting sets for the bottom program $\text{b}_U(P) = \{a \leftarrow \sim b. \ b \leftarrow \sim a.\}$. However, $\mathbb{P}_1$ can be viewed as the join of two NLP modules $\mathbb{Q}_1 = \langle \{a \leftarrow \sim b.\}, \{b\}, \{a\}, \emptyset \rangle$, and $\mathbb{Q}_2 = \langle \{b \leftarrow \sim a.\}, \{a\}, \{b\}, \emptyset \rangle$ to which the module theorem is applicable.

In the general case of SMOELS program modules we can use the module theorem to generalize the splitting-set theorem for SMOELS programs. Then the bottom module acts as an input generator for the top module, and one can simply find the stable models for the top module instantiated with the stable models of the bottom

module. The latter strategy used in Example 4.31 works even if there is negative recursion between the modules, as already shown in Example 4.18.

The module theorem strengthens an earlier version given in (Janhunen 2006) to cover programs that involve positive body literals, too. The independent sets proposed by Faber et al. (2005) push negative recursion inside modules which is unnecessary in view of our results. Their version of the module theorem is also weaker than Theorem 4.14.

The approach to modularity based on lp-functions (Gelfond and Gabaldon 1999; Baral 2003) has features similar to our approach. The components presented by lp-functions have an input/output interface and a *domain* reflecting the possible input interpretations. The functional specification requires an lp-function to have a *consistent answer set* for any interpretation in its domain. This is something that is not required in our module system. Lp-functions are flexible in the sense that there are several operators for refining them. However, the composition operator for lp-functions allows only incremental compositions, which again basically reflects the splitting-set theorem.

5 More on program (de)composition

So far we have established a module architecture for the class SMOLETS programs, in which modules interact through an input/output interface and the stable model semantics is fully compatible with the architecture. In this section we investigate further the ways to understand the internal structure of logic programs by seeing them as compositions of logic program modules. First, we use the conditions for module composition to introduce a method for decomposing an SMOLETS program into modules. A more detailed knowledge of the internal structure of a program (or a module) might reveal ways to improve search for stable models. Another application can be found in modularization of the translation-based equivalence verification method in (Oikarinen and Janhunen 2008b). Second, we consider possibilities of relaxing the conditions for module composition, that is, whether it is possible to allow positive recursion between modules in certain cases.

5.1 Finding a program decomposition

Recall that any SMOLETS program P can be viewed as a module $\langle P, \emptyset, \text{At}(P), \emptyset \rangle$, and thus we consider here a more general case of finding a module decomposition for an arbitrary SMOLETS program module $\mathbb{P} = \langle R, I, O, H \rangle$. The first step is to exploit the strongly connected components $D_1, \dots, D_n$ of $\text{Dep}^+(\mathbb{P})$ and define submodules $\mathbb{P}_i$ by grouping the rules so that for each D_i all the rules $r \in R$ such that $\text{Head}(r) \subseteq D_i$ are put into one submodule.

Now, the question is whether $\mathbb{P}_i$'s defined this way would form a valid decomposition of $\mathbb{P}$ into submodules. First notice that input atoms form a special case because $\text{Head}(R) \cap I = \emptyset$. Each $a \in I$ ends up in its own strongly connected component and there are no rules to include into a submodule corresponding to strongly connected component $\{a\}$. Thus it is actually unnecessary to include a submodule based on

such a component. Obviously, each weight rule in R goes into exactly one of the submodules. One should notice that for a choice rule $r \in R$ it can happen that $\text{Head}(r) \cap D_i \neq \emptyset$ and $\text{Head}(r) \cap D_j \neq \emptyset$ for $i \neq j$. This is not a problem, since it is always possible to *split a choice rule* by projecting the head, that is, by replacing a choice rule of the form $\{A\} \leftarrow B, \sim C$ with choice rules $\{A \cap D_i\} \leftarrow B, \sim C$ for each SCC D_i such that $A \cap D_i \neq \emptyset$.⁵

Based on the discussion above, we define the *set of rules defining a set of atoms* for an SMOELS program module.

Definition 5.1 *Given an SMOELS program module $\mathbb{P} = \langle R, I, O, H \rangle$ and a set of atoms $D \subseteq \text{At}(\mathbb{P}) \setminus I$, the set of rules defining D , denoted by $R[D]$, contains the following rules:*

- *a choice rule $\{A \cap D\} \leftarrow B, \sim C$ if and only if there is a choice rule $\{A\} \leftarrow B, \sim C$ in R such that $A \cap D \neq \emptyset$; and*
- *a weight rule $a \leftarrow w \leq \{B = W_B, \sim C = W_C\}$ if and only if there is a weight rule $a \leftarrow w \leq \{B = W_B, \sim C = W_C\}$ in R such that $a \in D$.*

We continue by defining a submodule of $\mathbb{P} = \langle R, I, O, H \rangle$ induced by a set of atoms $D \subseteq \text{At}(\mathbb{P}) \setminus I$. We use Definition 5.1 for the set of rules, and choose $D \cap O$ to be the output signature and the rest of the visible atoms appearing in $R[D]$ to be the input signature.

Definition 5.2 *Given an SMOELS program module $\mathbb{P} = \langle R, I, O, H \rangle$ and a set of atoms $D \subseteq \text{At}(\mathbb{P}) \setminus I$, a submodule induced by D is*

$$\mathbb{P}[D] = (R[D], (\text{At}(R[D]) \setminus D) \cap (I \cup O), D \cap O, D \cap H).$$

Let $D_1, \dots, D_m$ be the strongly connected components of $\text{Dep}^+(\mathbb{P})$ such that $D_i \cap I = \emptyset$. Now we can define $\mathbb{P}_i = \mathbb{P}[D_i]$ for each $1 \leq i \leq m$. Since the strongly connected components of $\text{Dep}^+(\mathbb{P})$ are used as a basis, it is guaranteed that there is no positive recursion between any of the submodules $\mathbb{P}_i$. Also, it is clear that the output signatures of the submodules are pairwise disjoint. Unfortunately this construction does not yet guarantee that hidden atoms stay local, and therefore the composition $\mathbb{P}_1 \oplus \dots \oplus \mathbb{P}_m$ might not be defined because certain $\mathbb{P}_i$'s might not respect each others hidden atoms.

A solution is to combine D_i 's in a way that modules will be closed with respect to dependencies caused by the hidden atoms, that is, if a hidden atom h belongs to a component D_i , then also all the atoms in the heads of rules in which h or $\sim h$ appears, have to belong to D_i , too. This can be achieved by finding the strongly connected components, denoted by $E_1, \dots, E_k$, for $\text{Dep}^h(\mathbb{P}, \{D_1, \dots, D_m\})$, where

⁵ Note that in the case of disjunctive logic programs, splitting a rule into two modules is more involved, see (Janhunen et al. 2007) for a discussion on a general shifting principle.

$\text{Dep}^h(\mathbb{P}, \{D_1, \dots, D_m\})$ has $\{D_1, \dots, D_m\}$ as the set of vertices, and

$$\{\langle D_i, D_j \rangle, \langle D_j, D_i \rangle \mid a \in D_i, b \in D_j, r \in R, \\ b \in \text{Head}(r) \text{ and } a \in \text{Body}(r) \cap \text{At}_h(\mathbb{P})\}$$

as the set of edges. Now, we take the sets

$$F_i = \bigcup_{D \in E_i} D$$

for $1 \leq i \leq k$ and use them to induce a module structure for $\mathbb{P}$ by defining $\mathbb{P}_i = \mathbb{P}[F_i]$ for $1 \leq i \leq k$.

As there may be atoms in $\text{At}(\mathbb{P})$ not appearing in the rules of $\mathbb{P}$, that is, $\text{At}(\mathbb{P}) = \text{At}(R)$ does not necessarily hold for $\mathbb{P} = \langle R, I, O, H \rangle$, it is possible that

$$\text{At}(\mathbb{P}) \setminus (\text{At}(\mathbb{P}_1) \cup \dots \cup \text{At}(\mathbb{P}_k)) \neq \emptyset.$$

To keep track of such atoms in $I \setminus \text{At}(R)$ we need an additional module defined as

$$\mathbb{P}_0 = \langle \emptyset, I \setminus \text{At}(R), \emptyset, \emptyset \rangle.$$

There is no need for a similar treatment for atoms in $(O \cup H) \setminus \text{At}(R)$ as each atom in $O \cup H$ belongs to some $\text{At}(\mathbb{P}_i)$ by definition.

Theorem 5.3 shows that we have a valid decomposition of $\mathbb{P}$ into submodules.

Theorem 5.3 *Consider an SMOLETS program module $\mathbb{P}$, and let $D_1, \dots, D_m$ be the SCCs of $\text{Dep}^+(\mathbb{P})$ such that $D_i \cap I = \emptyset$, and $E_1, \dots, E_k$ the strongly connected components of $\text{Dep}^h(\mathbb{P}, \{D_1, \dots, D_m\})$. Define $\mathbb{P}_0 = \langle \emptyset, I \setminus \text{At}(R), \emptyset, \emptyset \rangle$, and $\mathbb{P}_i = \mathbb{P}[F_i]$ for $F_i = \bigcup_{D \in E_i} D$ and $1 \leq i \leq k$. Then the join of the submodules $\mathbb{P}_i$ for $0 \leq i \leq k$ is defined and $\mathbb{P} \equiv_m \mathbb{P}_0 \sqcup \dots \sqcup \mathbb{P}_k$.*

Proof

Based on the construction of F_i 's and the discussion in this section it is clear that $\mathbb{P}' = \mathbb{P}_0 \sqcup \dots \sqcup \mathbb{P}_k$ is defined. It is easy to verify that the sets of input, output, and hidden atoms of modules $\mathbb{P}'$ and $\mathbb{P}$ are exactly the same. The only difference between the sets of rules in $\mathbb{P}$ and $\mathbb{P}'$ is that some choice rules in $\mathbb{P}$ may have been split into several rules in $\mathbb{P}'$. This is a syntactical change not affecting the stable models of the modules, that is, $\text{SM}(\mathbb{P}) = \text{SM}(\mathbb{P}')$. Notice also that $\text{Dep}^+(\mathbb{P}) = \text{Dep}^+(\mathbb{P}')$. Thus it holds that $\mathbb{P}' \equiv_m \mathbb{P}$. $\square$

5.2 Semantical conditions for module composition

Even though Example 4.9 shows that conditions for $\oplus$ are not enough to guarantee that the module theorem holds, there are cases where $\mathbb{P} \sqcup \mathbb{Q}$ is not defined and still it holds that $\text{SM}(\mathbb{P} \oplus \mathbb{Q}) = \text{SM}(\mathbb{P}) \bowtie \text{SM}(\mathbb{Q})$.

Example 5.4 *Consider modules $\mathbb{P} = \langle \{a \leftarrow b. a \leftarrow \sim c.\}, \{b\}, \{a, c\}, \emptyset \rangle$ and $\mathbb{Q} = \langle \{b \leftarrow a.\}, \{a\}, \{b\}, \emptyset \rangle$. Now, the composition*

$$\mathbb{P} \oplus \mathbb{Q} = \langle \{a \leftarrow b. a \leftarrow \sim c. b \leftarrow a.\}, \emptyset, \{a, b, c\}, \emptyset \rangle$$

is defined as the output sets are disjoint and there are no hidden atoms. Since $\text{SM}(\mathbb{P}) = \{\{a\}, \{a, b\}\}$ and $\text{SM}(\mathbb{Q}) = \{\emptyset, \{a, b\}\}$, we get $\text{SM}(\mathbb{P} \oplus \mathbb{Q}) = \{\{a, b\}\} = \text{SM}(\mathbb{P}) \bowtie \text{SM}(\mathbb{Q})$. ■

Example 5.4 suggests that the denial of positive recursion between modules can be relaxed in certain cases. We define a semantical characterization for module composition that maintains the compositionality of the stable model semantics.

Definition 5.5 *The semantical join $\mathbb{P}_1 \sqcup \mathbb{P}_2$ of two SMOLETS program modules $\mathbb{P}_1$ and $\mathbb{P}_2$ is $\mathbb{P}_1 \oplus \mathbb{P}_2$, provided $\mathbb{P}_1 \oplus \mathbb{P}_2$ is defined and $\text{SM}(\mathbb{P}_1 \oplus \mathbb{P}_2) = \text{SM}(\mathbb{P}_1) \bowtie \text{SM}(\mathbb{P}_2)$.*

The module theorem holds by definition for SMOLETS program modules composed with $\sqcup$. We can now present an alternative formulation for modular equivalence taking features from strong equivalence (Lifschitz et al. 2001).

Definition 5.6 *SMOLETS program modules $\mathbb{P}$ and $\mathbb{Q}$ are semantically modularly equivalent, denoted by $\mathbb{P} \equiv_{\text{sem}} \mathbb{Q}$, if and only if $\text{At}_i(\mathbb{P}) = \text{At}_i(\mathbb{Q})$ and $\mathbb{P} \sqcup \mathbb{R} \equiv_v \mathbb{Q} \sqcup \mathbb{R}$ for all $\mathbb{R}$ such that $\mathbb{P} \sqcup \mathbb{R}$ and $\mathbb{Q} \sqcup \mathbb{R}$ are defined.*

It is straightforward to see that $\equiv_{\text{sem}}$ is a congruence for $\sqcup$ and reduces to $\equiv_v$ for modules with completely specified input, that is, modules $\mathbb{P}$ such that $\text{At}_i(\mathbb{P}) = \emptyset$.

Theorem 5.7 *$\mathbb{P} \equiv_m \mathbb{Q}$ if and only if $\mathbb{P} \equiv_{\text{sem}} \mathbb{Q}$ for any SMOLETS program modules $\mathbb{P}$ and $\mathbb{Q}$.*

Proof

Assume $\mathbb{P} \equiv_{\text{sem}} \mathbb{Q}$. Now, $\mathbb{P} \equiv_m \mathbb{Q}$ is implied by Definition 5.6 with empty context module $\mathbb{R} = \langle \emptyset, \emptyset, \emptyset, \emptyset \rangle$. Assume then $\mathbb{P} \equiv_m \mathbb{Q}$, that is, there is a bijection $f : \text{SM}(\mathbb{P}) \rightarrow \text{SM}(\mathbb{Q})$ such that for each $M \in \text{SM}(\mathbb{P})$, $M \cap \text{At}_v(\mathbb{P}) = f(M) \cap \text{At}_v(\mathbb{Q})$. Consider arbitrary $\mathbb{R}$ such that $\mathbb{P} \sqcup \mathbb{R}$ and $\mathbb{Q} \sqcup \mathbb{R}$ are defined. Then $\text{SM}(\mathbb{P} \sqcup \mathbb{R}) = \text{SM}(\mathbb{P}) \bowtie \text{SM}(\mathbb{R})$ and $\text{SM}(\mathbb{Q} \sqcup \mathbb{R}) = \text{SM}(\mathbb{Q}) \bowtie \text{SM}(\mathbb{R})$.

We now define $g : \text{SM}(\mathbb{P} \sqcup \mathbb{R}) \rightarrow \text{SM}(\mathbb{Q} \sqcup \mathbb{R})$ such that for any $M \in \text{SM}(\mathbb{P} \sqcup \mathbb{R})$,

$$g(M) = f(M_P) \cup M_R,$$

where $M = M_P \cup M_R$ such that $M_P \in \text{SM}(\mathbb{P})$ and $M_R \in \text{SM}(\mathbb{R})$ are compatible. Now, g is a bijection and $M \cap (\text{At}_v(\mathbb{P}) \cup \text{At}_v(\mathbb{R})) = g(M) \cap (\text{At}_v(\mathbb{Q}) \cup \text{At}_v(\mathbb{R}))$ for each $M \in \text{SM}(\mathbb{P} \sqcup \mathbb{R})$. Since $\mathbb{R}$ was arbitrary, $\mathbb{P} \equiv_{\text{sem}} \mathbb{Q}$ follows. □

Theorem 5.7 implies that $\equiv_m$ is a congruence for $\sqcup$, too. Thus it is possible to replace $\mathbb{P}$ with modularly equivalent $\mathbb{Q}$ in the contexts allowed by $\sqcup$.

The syntactical restriction denying positive recursion between modules is easy to check, since SCCs can be found in a linear time with respect to the size of the dependency graph (Tarjan 1972). To the contrary, checking whether $\text{SM}(\mathbb{P}_1 \oplus \mathbb{P}_2) = \text{SM}(\mathbb{P}_1) \bowtie \text{SM}(\mathbb{P}_2)$ is a computationally harder problem.

Theorem 5.8 *Given SMOLETS program modules $\mathbb{P}_1$ and $\mathbb{P}_2$ such that $\mathbb{P}_1 \oplus \mathbb{P}_2$ is defined, deciding whether it holds that $\text{SM}(\mathbb{P}_1 \oplus \mathbb{P}_2) = \text{SM}(\mathbb{P}_1) \bowtie \text{SM}(\mathbb{P}_2)$ is a coNP-complete decision problem.*

Proof

Let $\mathbb{P}_1$ and $\mathbb{P}_2$ be SMOBELS program modules such that $\mathbb{P}_1 \oplus \mathbb{P}_2$ is defined. We can show $\text{SM}(\mathbb{P}_1 \oplus \mathbb{P}_2) \neq \text{SM}(\mathbb{P}_1) \bowtie \text{SM}(\mathbb{P}_2)$ by choosing $M \subseteq \text{At}(\mathbb{P}_1 \oplus \mathbb{P}_2)$ and checking that

- $M \in \text{SM}(\mathbb{P}_1 \oplus \mathbb{P}_2)$ and $M \cap \text{At}(\mathbb{P}_1) \notin \text{SM}(\mathbb{P}_1)$; or
- $M \in \text{SM}(\mathbb{P}_1 \oplus \mathbb{P}_2)$ and $M \cap \text{At}(\mathbb{P}_2) \notin \text{SM}(\mathbb{P}_2)$; or
- $M \notin \text{SM}(\mathbb{P}_1 \oplus \mathbb{P}_2)$, $M \cap \text{At}(\mathbb{P}_1) \in \text{SM}(\mathbb{P}_1)$, and $M \cap \text{At}(\mathbb{P}_2) \in \text{SM}(\mathbb{P}_2)$.

Once we have chosen M , these tests can be performed in polynomial time, which shows that the problem is in **coNP**. To establish **coNP**-hardness we present a reduction from **3SAT**. Consider a finite set $S = \{C_1, \dots, C_n\}$ of three-literal clauses C_i of the form $l_1 \vee l_2 \vee l_3$ where each l_i is either an atom a or its classical negation $\neg a$. Each clause C_i is translated into rules $r_{i,j}$ of the form $c_i \leftarrow f_j$, where $1 \leq j \leq 3$, and $f_j = a$ if $l_j = a$ and $f_j = \neg a$ if $l_j = \neg a$. The intuitive reading of c_i is that clause C_i is satisfied. We define modules $\mathbb{P}_1 = \langle \{e \leftarrow d.\}, \{d\}, \{e\}, \emptyset \rangle$ and

$$\mathbb{P}_2 = \langle \{r_{i,j} \mid 1 \leq i \leq n, 1 \leq j \leq 3\} \cup \{d \leftarrow e, c_1, \dots, c_n.\}, \text{At}(S) \cup \{e\}, \{d\}, \{c_1, \dots, c_n\} \rangle.$$

Now $\mathbb{P}_1 \oplus \mathbb{P}_2$ is defined, and $\text{SM}(\mathbb{P}_1) = \{\emptyset, \{d, e\}\}$. There is $M \in \text{SM}(\mathbb{P}_2)$ that is compatible with $\{d, e\}$ if and only if $S \in \text{3SAT}$. Since $d \notin N$ and $e \notin N$ for all $N \in \text{SM}(\mathbb{P}_1 \oplus \mathbb{P}_2)$, it follows that $S \in \text{3SAT}$ if and only if $\text{SM}(\mathbb{P}_1 \oplus \mathbb{P}_2) = \text{SM}(\mathbb{P}_1) \bowtie \text{SM}(\mathbb{P}_2)$. $\square$

Theorem 5.8 shows that there is a tradeoff for allowing positive recursion between modules, as more effort is needed to check that composition of such modules does not compromise the compositionality of the stable model semantics.

6 Tools and Practical Demonstration

The goal of this section is to demonstrate how the module system introduced in Section 4 can be exploited in practise in the context of the SMOBELS system and other compatible systems. In this respect, we present tools that have been developed for the (de)composition of logic programs that are represented in the *internal file format*⁶ of the SMOBELS engine. The binaries for both tools are available under the ASPTOOLS collection⁷. Moreover, we conduct and report a practical experiment which illustrates the performance of the tools when processing substantially large benchmark instances, that is, SMOBELS programs having up to millions of rules (see the ASPTOOLS web page for examples).

The first tool, namely MODLIST, is targeted at program decomposition based on the strongly connected components of an SMOBELS program given as input. In view of the objectives of Section 5.1, there are three optional outcomes of the decomposition, that is, strongly connected components that take into account

⁶ The reader is referred to (Janhunen 2007) for a detailed description and analysis of the format.

⁷ <http://www.tcs.hut.fi/Software/asptools/>

1. positive dependencies only,
2. positive dependencies and hidden atoms, and
3. both positive and negative dependencies as well as hidden atoms.

The number of modules created by MODLIST decreases in this order. However, our benchmarks cover program instances that get split in tens of thousands of modules. To tackle the problem of storing such numbers of modules in separate files we decided to use file compression and packaging tools and, in particular, the ZIP utility available in standard Linux installations. We found ZIP superior to TAR as it allows random access to files in an archive, or a *zipfile*. This feature becomes valuable when the modules are accessed from the archive for further processing.

The tool for program composition has been named as LPCAT which refers to the concatenation of files containing logic programs. A new version of the tool was implemented for experiments reported below for better performance as well as usability. The old version (version 1.8) is only able to combine two modules at a time which gives a quadratic nature for a process of combining n modules together: modules are added one-by-one to the composition. The new version, however, is able to read in modules from several files and, even more conveniently, a *stream of modules* from an individual file. The ZIP facility provides an option for creating such a stream that can then be forwarded for LPCAT for composition. This is the strategy for composing programs in experiments that are described next.

To test the performance of our tools, we picked a set of benchmark instances having from tens of thousands up to millions of rules—expressed in the SMOELS format. For each instance, the first task is to decompose the instance into modules using MODLIST and to create a zipfile containing the modules. The type of modules to be created is varied according the three schemes summarized above. The second task is to recreate the benchmark instance from a stream of modules extracted from the respective zipfile. As suggested above, the actual composition is carried out using LPCAT and we also check that the number of rules matches with the original instance. Due to high number of rules, checking the equivalence of the original and composed programs (Janhunen and Oikarinen 2007) is unfeasible in many cases. If all atoms are visible, this can be accomplished syntactically on the basis of sorted textual representations of the programs involved. To ensure that MODLIST and LPCAT produce correct (de)compositions of programs, such a check was performed for all compositions created for the first three benchmarks which involve no hidden atoms. As regards computer hardware, we run MODLIST and LPCAT on a PC with a 1.8GHz Intel Core 2 Duo CPU and 2GBs of main memory—operating under the Linux 2.6.18 system. In experimental results collected in Table 1, we report the sum of user and system times that are measured with the `/usr/bin/time` command. There are three benchmark types (**bt** for short) as enumerated in the beginning of this section. We refer to them using the respective abbreviations $+$, $+h$, and $\pm h$.

The first benchmark instance in Table 1, viz. *ephp-13*, is a formalization (Järvisalo and Oikarinen 2007) of the classical *pigeon hole principle* for 13 pigeons—extended by redundant rules in analogy to Tseitin’s *extended resolution* proof system. This program can be deemed medium-sized within our benchmarks. There are no hidden atoms, no positive re-

Benchmark	na	nr	bt	nm	dt (s)	ct (s)
ephp-13	35 518	90 784	+	35 518	2 110	362
			+h	35 518	2 110	362
			±h	35 362	2 090	361
mutex3	276 086	2 406 357	+	101 819	22 900	9 570
			+h	101 819	23 300	9 640
			±h	101 609	24 000	9 580
phi3	7 379	14 274	+	6 217	74,3	3,32
			+h	6 217	74,3	3,35
			±h	5 686	63,2	2,92
seq4-ss4	6 873	1 197 182	+	3 425	121	60,0
			+h	1 403	89,4	31,9
			±h	107	20,2	7,58

Legends for abbreviations: **na**: Number of atoms
nr: Number of rules
nm: Number of modules
bt: Benchmark type
dt: Decomposition time
ct: Composition time

Table 1. Summary of benchmark results for module (de)composition

cursion and little negative recursion in this program instance as indicated by the number of atoms (35 518) and the respective numbers of modules (see column **nm**). Thus we have an example of a very fine-grained decomposition where the *definition*⁸ of each atom ends up as its own module in the outcome. The given timings indicate that MODLIST and LPCAT are able to handle 15 and 100 modules per second, respectively. The share of file I/O and (de)compression is substantial in program decomposition. For instance, the actual splitting of the *ephp-13* benchmark (+h) using MODLIST takes only 0,59 seconds—the rest of approximately 2110 seconds is spent to create the zipfile. To the contrary, inflating the stream of modules from the zipfile is very efficient as it takes only 0,45 seconds in case of *ephp-13*. After that the restoration of the original program instance takes roughly 361 seconds. The creation and compression of a joint symbol table for the modules accounts for the most of the time spent on this operation. It should also be stressed that it is impractical to store modules in separate files for this program. For instance, a shell command that refers to all modules fails due to excessive number of arguments at the respective command line.

The next two programs in Table 1, *mutex3* and *phi3*, are related to the *distributed*

⁸ The set of rules that mention the atom in question in their head.

implementability problem of asynchronous automata, and particular formalizations of classical *mutual exclusion* and *dining philosophers* problems (Heljanko and Ştefănescu 2004; Heljanko and Ştefănescu 2005). These programs involve no hidden atoms and both positive and negative interdependencies of atoms occur. The extremely high numbers of rules (2406357) and modules (101819) are clearly reflected in running times perceived for *mutex3*. However, the respective rates of 4 and 10 modules per second do not differ too much from those obtained for *ephp-13* given the fact that the number of rules is about 25 times higher. The data observed for *phi3* is analogous to those obtained for *ephp-13* and *mutex3* but the respective modules-per-second rates are much higher: approximately 90 and 2000. This may partly boil down to the fact *phi3* is the smallest program under consideration and it has also the smallest number of rules per module ratio.

Our last benchmark program, *seq4-ss4*, is taken from benchmark sets of (Brain et al. 2006) where the optimization of machine code using ASP techniques is of interest. The program in question formalizes the optimization of a particular sequence of four SPARC-v7 instructions. This program instance has the greatest modules as regards the number of rules—the average number of rules per module varies from about 350 to 11200 depending on the module type. It has also hidden atoms which makes a difference between modules based on plain SCCs and their combinations induced by the dependencies caused by the use of hidden atoms. The respective modules-per-second rates 28, 19, and 5 are all better than 4 obtained for *mutex3*.

To provide the reader with a better idea of sizes of individual modules, we have collected some numbers about their distribution in Table 2. Each program involves a substantial number of modules with just one rule each of which defines a single atom of interest. On the other hand, the largest SCCs for *ephp-13*, *mutex3*, *phi3*, and *seq4-ss4* involve 949, 2091912, 2579, and 1071689 rules, respectively. For *mutex3*, the biggest module consists of a definition of an equivalence relation over states in the verification domain—creating a huge set of positively interdependent atoms. For *ephp-13*, the greatest module is a collection of nogoods which can be shown to have no stable models in roughly 99500 seconds using SMOELS (version 2.32). However, the remaining rules of *ephp-13* make this fact much faster to prove: only 61 seconds elapse.

A few concluding remarks follow. Increasing the number of modules in a program tends to decrease the number of modules that can be decomposed per time unit. This observation suggests that the creation of the zipfile has a quadratic flavor although modules themselves can be figured out in linear time (using a variant of Tarjan’s algorithm). Perhaps this can be improved in the future by better integrating the creation of the zipfile into MODLIST. For now, it creates a shell script for this purpose. Handling the biggest program instances is also subject to the effects of memory allocation which may further slow down computations. On the other hand, the cost of increasing the number of rules in modules seems to be relatively small. Moreover, it is clear on the basis of data given in Table 1 that the composition of programs is faster than decomposition. This would not be the case if the old version of LPCAT were used for composition. Last, we want to emphasize that MODLIST and LPCAT have been implemented as supplementary tools that are not directly related

Benchmark	ephp-13	mutex3	phi3	seq-ss4
nr	nm			
1	14 474	67 749	2 811	2 969
2	7 014	2 757	1 434	
3–4	12 680	41	1 962	
5–8	149	30 798	2	
9–16	618	255	6	
17–32	582			11
33–64			1	
65–128				134
129–512				296
513–1 024	1			9
over 1 024		2	1	2

Table 2. Distribution of the sizes of modules (see Table 1 for legends)

to the computation of stable models. Nevertheless, we intend to exploit these tools in order to modularize different tasks in ASP such as verifying ordinary/modular equivalence and program optimization. The existence of such tools enables modular program development and the creation of *module libraries* for SMOLETS programs, and thus puts forward the use of module architectures in the realm of ASP.

7 Conclusions

In this paper, we introduce a simple and intuitive notion of a logic program module that interacts with other modules through a well-defined input/output interface. The design has its roots in a module architecture proposed for conventional logic programs (Gaifman and Shapiro 1989), but as regards our contribution, we tailor the architecture in order to better meet the criteria of ASP. Perhaps the most important objective in this respect is to achieve the compositionality of stable model semantics, that is, the semantics of an entire program depends directly on the semantics assigned to its modules. To this end, the main result of this paper is formalized as the *module theorem* (Theorem 4.14) which links program-level stability with module-level stability. The theorem holds under the assumption that positively interdependent atoms are always placed in the same module. The *join* operation $\sqcup$ defined for program modules effectively formalizes this constraint—which we find acceptable when it comes to good programming style in ASP.

The module theorem is also a proper generalization of the splitting-set theorem (Lifschitz and Turner 1994) recast for SMOLETS programs. The main difference is that splitting-sets do not enable any kind of recursion between modules. Even though the module theorem is proved to demonstrate the feasibility of the respective module architecture, it is also applied as a tool to simplify mathematical proofs in this paper and recently also in (Oikarinen and Janhunen 2008a;

Oikarinen and Janhunen 2008b). It also lends itself to extensions for further classes of logic programs which can be brought into effect in terms of *strongly faithful*, $\sqcup$ -*preserving*, and *modular* translations for the removal of new syntax (Theorem 4.28). Moreover, the module theorem paves the way for the modularization of various reasoning tasks, such as search for answer sets, query evaluation, and verification, in ASP.

The second main theme of the paper is the notion of modular equivalence which is proved to be a proper congruence relation for program composition using $\sqcup$ (Theorem 4.20). Thus modular equivalence is preserved under substitutions of modularly equivalent program modules. Since uniform equivalence is not a congruence for ordinary $\cup$ but strong equivalence is by definition, modular equivalence can be viewed as a reasonable compromise between these two extremes. In addition to the congruence property, we present a number of results about modular equivalence.

1. We show that deciding modular equivalence forms a **coNP**-complete decision problem for SMOBELS program modules with the EVA property, that is, those having enough visible atoms so that their stable models can be distinguished from each other on the basis of visible atoms only. In this way, it is possible to use the SMOBELS solver for the actual verification task.
2. We consider the possibility of redefining the join operation $\sqcup$ using a semantical condition that corresponds to the content of the module theorem. The notion of modular equivalence is not affected, but the cost of verifying whether a particular join of modules is defined becomes a **coNP**-complete decision problem. This is in contrast with the linear time check for positive recursion (Tarjan's algorithm for strongly connected components) but it may favorably extend the coverage of modular equivalence in certain applications.
3. Finally, we also analyze the problem of decomposing an SMOBELS program into modules when there is no a priori knowledge about the structure of the program. The strongly connected components of the program provide the starting point in this respect, but the usage of hidden atoms may enforce a higher degree of amalgamation when the modules of a program are extracted.

The theoretical results presented in the paper have emerged in close connection with the development of tools for ASP. The practical demonstration in Section 6 illustrates the basic facilities that are required to deal with *object level* modules within the SMOBELS system.⁹ The linker, namely LPCAT, enables the composition of ground programs in the SMOBELS format. Using this tool, for instance, it is possible to add a query to a program afterwards without grounding the program again. On the other hand, individual modules of a program can be accessed from the zipfile created by the module extractor MODLIST. This is highly practical since we intend to pursue techniques for module-level optimization in the future.

⁹ Likewise, source level modules could be incorporated to the front-end of the system (LPARSE).

Acknowledgements

This work has been partially supported by the Academy of Finland through Projects #211025 and #122399. The first author gratefully acknowledges the financial support from Helsinki Graduate School in Computer Science and Engineering, Emil Aaltonen Foundation, the Finnish Foundation for Technology Promotion TES, the Nokia Foundation, and the Finnish Cultural Foundation.

Appendix A Proofs

Proof of Theorem 4.20

Let $\mathbb{P}$ and $\mathbb{Q}$ be modules such that $\mathbb{P} \equiv_m \mathbb{Q}$. Let $\mathbb{R}$ be an arbitrary module such that $\mathbb{P} \sqcup \mathbb{R}$ and $\mathbb{Q} \sqcup \mathbb{R}$ are defined. From $\text{At}_v(\mathbb{P}) = \text{At}_v(\mathbb{Q})$ and $\text{At}_i(\mathbb{P}) = \text{At}_i(\mathbb{Q})$ it follows that $\text{At}_v(\mathbb{P} \sqcup \mathbb{R}) = \text{At}_v(\mathbb{Q} \sqcup \mathbb{R})$ and $\text{At}_i(\mathbb{P} \sqcup \mathbb{R}) = \text{At}_i(\mathbb{Q} \sqcup \mathbb{R})$.

Consider any model $M \in \text{SM}(\mathbb{P} \sqcup \mathbb{R})$. By Theorem 4.14, $\text{SM}(\mathbb{P} \sqcup \mathbb{R}) = \text{SM}(\mathbb{P}) \ltimes \text{SM}(\mathbb{R})$, that is, $M_P = M \cap \text{At}(\mathbb{P}) \in \text{SM}(\mathbb{P})$ and $M_R = M \cap \text{At}(\mathbb{R}) \in \text{SM}(\mathbb{R})$. Since $\mathbb{P} \equiv_m \mathbb{Q}$, there is a bijection $f : \text{SM}(\mathbb{P}) \rightarrow \text{SM}(\mathbb{Q})$ such that $M_P \in \text{SM}(\mathbb{P}) \iff f(M_P) \in \text{SM}(\mathbb{Q})$, and

$$M_P \cap \text{At}_v(\mathbb{P}) = f(M_P) \cap \text{At}_v(\mathbb{Q}). \quad (\text{A1})$$

Denote $M_Q = f(M_P)$. Clearly, M_P and M_R are compatible. Since (A1) holds, also M_Q and M_R are compatible. Applying Theorem 4.14 we get $M_Q \cup M_R \in \text{SM}(\mathbb{Q} \sqcup \mathbb{R}) = \text{SM}(\mathbb{Q}) \ltimes \text{SM}(\mathbb{R})$.

Now, define a function $g : \text{SM}(\mathbb{P} \sqcup \mathbb{R}) \rightarrow \text{SM}(\mathbb{Q} \sqcup \mathbb{R})$ as

$$g(M) = f(M \cap \text{At}(\mathbb{P})) \cup (M \cap \text{At}(\mathbb{R})).$$

Clearly, g maps the set of visible atoms in M to itself, that is,

$$M \cap (\text{At}_v(\mathbb{P} \sqcup \mathbb{R})) = g(M) \cap (\text{At}_v(\mathbb{Q} \sqcup \mathbb{R})).$$

Function g is a bijection, since

- g is an injection: $M \neq N$ implies $g(M) \neq g(N)$ for all $M, N \in \text{SM}(\mathbb{P} \sqcup \mathbb{R})$, since $f(M \cap \text{At}(\mathbb{P})) \neq f(N \cap \text{At}(\mathbb{P}))$ or $M \cap \text{At}(\mathbb{R}) \neq N \cap \text{At}(\mathbb{R})$.
- g is a surjection: for any $M \in \text{SM}(\mathbb{Q} \sqcup \mathbb{R})$, $N = f^{-1}(M \cap \text{At}(\mathbb{Q})) \cup (M \cap \text{At}(\mathbb{R})) \in \text{SM}(\mathbb{P} \sqcup \mathbb{R})$ and $g(N) = M$, since f is a surjection.

The inverse function $g^{-1} : \text{SM}(\mathbb{Q} \sqcup \mathbb{R}) \rightarrow \text{SM}(\mathbb{P} \sqcup \mathbb{R})$ can be defined as $g^{-1}(N) = f^{-1}(N \cap \text{At}(\mathbb{Q})) \cup (N \cap \text{At}(\mathbb{R}))$. Thus $\mathbb{P} \sqcup \mathbb{R} \equiv_m \mathbb{Q} \sqcup \mathbb{R}$. $\square$

Proof of Theorem 4.26

We present an alternative proof to the one given in (Oikarinen and Janhunen 2006). We use the characterization of stable models based on the programs completion and loop formulas presented in Theorem 3.10.

First, we need to generalize the concepts of completion and loop formulas for NLP modules. Given a normal logic program module $\mathbb{P} = \langle R, I, O, H \rangle$, we define

$$\text{Comp}(\mathbb{P}) = \bigwedge_{a \in O \cup H} \left(a \leftrightarrow \bigvee_{\text{Head}(r)=a} \left(\bigwedge_{b \in \text{Body}^+(r)} b \wedge \bigwedge_{c \in \text{Body}^-(r)} \neg c \right) \right), \quad (\text{A2})$$

that is, we take the completion in the normal way for the set of rules R with the exception that we take into account that input atoms do not have any defining rules. As regards loop formulas, we define $\text{LF}(\mathbb{P}) = \text{LF}(R)$, since no atom in the input signature can appear in any of the loops.

Consider an arbitrary NLP module $\mathbb{P} = \langle R, I, O, H \rangle$. Define a set of rules, that is, a conventional normal logic program, $R' = R \cup G_I$, where $G_I = \{a \leftarrow \sim \bar{a} \mid \bar{a} \leftarrow \sim a \mid a \in I\}$ and all atoms $\bar{a}$ are new atoms not appearing in $\text{At}(\mathbb{P})$. Now, $M \in \text{SM}(\mathbb{P})$ if and only if $N = M \cup \{\bar{a} \mid a \in I \setminus M\} \in \text{SM}(R')$. On the other hand, by Theorem 3.10, $N \in \text{SM}(R')$ if and only if $N \models \text{Comp}(R') \cup \text{LF}(R')$. Considering the completion, since $\text{Head}(R) \cap I = \emptyset$, and atoms $\bar{a}$ are new, it holds that $\text{Comp}(R') = \text{Comp}(\mathbb{P}) \cup \text{Comp}(G_I)$. As regards loop formulas, we notice that $\text{Dep}^+(R')$ is $\text{Dep}^+(R)$ together with vertices for atoms $\{\bar{a} \mid a \in I\}$, which have no edges in $\text{Dep}^+(R')$. Therefore, $\text{LF}(R') = \text{LF}(R) = \text{LF}(\mathbb{P})$.

Thus $N \models \text{Comp}(R') \cup \text{LF}(R')$ if and only if $N \models \text{Comp}(\mathbb{P}) \cup \text{Comp}(G_I) \cup \text{LF}(\mathbb{P})$. Furthermore, based on the relationship between M and N , it holds that $N \models \text{Comp}(\mathbb{P}) \cup \text{Comp}(G_I) \cup \text{LF}(\mathbb{P})$ if and only if $M \models \text{Comp}(\mathbb{P}) \cup \text{LF}(\mathbb{P})$. Thus Theorem 3.10 generalizes directly for NLP modules: given a normal logic program module $\mathbb{P}$ and an interpretation $M \subseteq \text{At}(\mathbb{P})$, it holds that $M \in \text{SM}(\mathbb{P})$ if and only if $M \models \text{Comp}(\mathbb{P}) \cup \text{LF}(\mathbb{P})$.

Now, since the join operation does not allow positive recursion between two modules, and $(\text{At}_o(\mathbb{P}_1) \cup \text{At}_h(\mathbb{P}_1)) \cap (\text{At}_o(\mathbb{P}_2) \cup \text{At}_h(\mathbb{P}_2)) = \emptyset$, it holds that

$$\text{Comp}(\mathbb{P}_1 \sqcup \mathbb{P}_2) = \text{Comp}(\mathbb{P}_1) \cup \text{Comp}(\mathbb{P}_2), \text{ and} \quad (\text{A3})$$

$$\text{LF}(\mathbb{P}_1 \sqcup \mathbb{P}_2) = \text{LF}(\mathbb{P}_1) \cup \text{LF}(\mathbb{P}_2). \quad (\text{A4})$$

Furthermore, the satisfaction relation is compositional for $\sqcup$, that is, $M \models P \sqcup Q$ if and only if $M \cap \text{At}(P) \models P$ and $M \cap \text{At}(Q) \models Q$ for any propositional theories P and Q . Thus

$$\begin{aligned} M \in \text{SM}(\mathbb{P}_1 \sqcup \mathbb{P}_2) &\iff M \models \text{Comp}(\mathbb{P}_1 \sqcup \mathbb{P}_2) \cup \text{LF}(\mathbb{P}_1 \sqcup \mathbb{P}_2) \\ &\iff M \models \text{Comp}(\mathbb{P}_1) \cup \text{Comp}(\mathbb{P}_2) \cup \text{LF}(\mathbb{P}_1) \cup \text{LF}(\mathbb{P}_2) \\ &\iff M \cap \text{At}(\mathbb{P}_1) \models \text{Comp}(\mathbb{P}_1) \cup \text{LF}(\mathbb{P}_1) \text{ and} \\ &\quad M \cap \text{At}(\mathbb{P}_2) \models \text{Comp}(\mathbb{P}_2) \cup \text{LF}(\mathbb{P}_2) \\ &\iff M \cap \text{At}(\mathbb{P}_1) \in \text{SM}(\mathbb{P}_1) \text{ and } M \cap \text{At}(\mathbb{P}_2) \in \text{SM}(\mathbb{P}_2). \end{aligned}$$

It follows that $\text{SM}(\mathbb{P}_1 \sqcup \mathbb{P}_2) = \text{SM}(\mathbb{P}_1) \bowtie \text{SM}(\mathbb{P}_2)$. $\square$

Proof of Theorem 4.28

Let $\mathcal{C}_1$ and $\mathcal{C}_2$ be two classes of logic program modules such that $\mathcal{C}_2 \subseteq \mathcal{C}_1$, and the module theorem holds for modules in $\mathcal{C}_2$. Consider a translation function $\text{Tr}: \mathcal{C}_1 \rightarrow \mathcal{C}_2$ such that Conditions 1–3 from Definition 4.27 are satisfied. Let $\mathbb{P}_1, \mathbb{P}_2 \in \mathcal{C}_1$ be modules such that $\mathbb{P}_1 \sqcup \mathbb{P}_2$ is defined. Then Condition 2 implies that $\text{Tr}(\mathbb{P}_1), \text{Tr}(\mathbb{P}_2) \in \mathcal{C}_2$ are modules such that $\text{Tr}(\mathbb{P}_1) \sqcup \text{Tr}(\mathbb{P}_2)$ is defined. Since the module theorem holds for modules in $\mathcal{C}_2$, $\text{SM}(\text{Tr}(\mathbb{P}_1) \sqcup \text{Tr}(\mathbb{P}_2)) = \text{SM}(\text{Tr}(\mathbb{P}_1)) \bowtie \text{SM}(\text{Tr}(\mathbb{P}_2))$. Moreover, Condition 3 implies that $\text{SM}(\text{Tr}(\mathbb{P}_1 \sqcup \mathbb{P}_2)) = \text{SM}(\text{Tr}(\mathbb{P}_1) \sqcup \text{Tr}(\mathbb{P}_2))$.

Condition 1 implies there is a bijection

$$g : \quad \text{SM}(\mathbb{P}_1 \sqcup \mathbb{P}_2) \rightarrow \text{SM}(\text{Tr}(\mathbb{P}_1 \sqcup \mathbb{P}_2))$$

such that for any $M \in \text{SM}(\mathbb{P}_1 \sqcup \mathbb{P}_2)$ we have $M = g(M) \cap \text{At}(\mathbb{P}_1 \sqcup \mathbb{P}_2)$. Notice that strong faithfulness requires that the projections of M and $g(M)$ have to be identical over whole $\text{At}(\mathbb{P}_1 \sqcup \mathbb{P}_2)$ not just over $\text{At}_v(\mathbb{P}_1 \sqcup \mathbb{P}_2)$. Similarly there are bijections

$$\begin{aligned} g_1 : \quad & \text{SM}(\mathbb{P}_1) \rightarrow \text{SM}(\text{Tr}(\mathbb{P}_1)) \text{ and} \\ g_2 : \quad & \text{SM}(\mathbb{P}_2) \rightarrow \text{SM}(\text{Tr}(\mathbb{P}_2)) \end{aligned}$$

such that for any $M_i \in \text{SM}(\mathbb{P}_i)$ ($i = 1, 2$) it holds that $M_i = g_i(M_i) \cap \text{At}(\mathbb{P}_i)$. Consider arbitrary $M \subseteq \text{At}(\mathbb{P}_1 \sqcup \mathbb{P}_2)$, and its projections $M_1 = M \cap \text{At}(\mathbb{P}_1)$ and $M_2 = M \cap \text{At}(\mathbb{P}_2)$. Now, M_1 and M_2 are compatible, and $M = M_1 \cup M_2$.

Assume that $M \in \text{SM}(\mathbb{P}_1 \sqcup \mathbb{P}_2)$. Since the module theorem holds for $\mathcal{C}_2$, we have

$$g(M) \in \text{SM}(\text{Tr}(\mathbb{P}_1 \sqcup \mathbb{P}_2)) = \text{SM}(\text{Tr}(\mathbb{P}_1) \sqcup \text{Tr}(\mathbb{P}_2)) = \text{SM}(\text{Tr}(\mathbb{P}_1)) \bowtie \text{SM}(\text{Tr}(\mathbb{P}_2)),$$

that is,

$$\begin{aligned} N_1 &= g(M) \cap \text{At}(\text{Tr}(\mathbb{P}_1)) \in \text{SM}(\text{Tr}(\mathbb{P}_1)), \\ N_2 &= g(M) \cap \text{At}(\text{Tr}(\mathbb{P}_2)) \in \text{SM}(\text{Tr}(\mathbb{P}_2)), \text{ and} \end{aligned}$$

N_1 and N_2 are compatible projections of $g(M)$. Moreover, $M = g(M) \cap \text{At}(\mathbb{P}_1 \sqcup \mathbb{P}_2)$ and $M_i = N_i \cap \text{At}(\mathbb{P}_i)$ for $i = 1, 2$. Using the inverse functions of g_1 and g_2 we get $M_1 = g_1^{-1}(N_1) \in \text{SM}(\mathbb{P}_1)$ and $M_2 = g_2^{-1}(N_2) \in \text{SM}(\mathbb{P}_2)$.

For the other direction, assume that $M_1 \in \text{SM}(\mathbb{P}_1)$ and $M_2 \in \text{SM}(\mathbb{P}_2)$. Then $N_1 = g_1(M_1) \in \text{SM}(\text{Tr}(\mathbb{P}_1))$ and $N_2 = g_2(M_2) \in \text{SM}(\text{Tr}(\mathbb{P}_2))$. Since

$$\begin{aligned} N_1 \cap \text{At}_v(\text{Tr}(\mathbb{P}_2)) &= M_1 \cap \text{At}_v(\mathbb{P}_2), \\ N_2 \cap \text{At}_v(\text{Tr}(\mathbb{P}_1)) &= M_2 \cap \text{At}_v(\mathbb{P}_1), \text{ and} \end{aligned}$$

M_1 and M_2 are compatible, also N_1 and N_2 are compatible. By applying the module theorem for $\mathcal{C}_2$, we get $N = N_1 \cup N_2 \in \text{SM}(\text{Tr}(\mathbb{P}_1) \sqcup \text{Tr}(\mathbb{P}_2)) = \text{SM}(\text{Tr}(\mathbb{P}_1 \sqcup \mathbb{P}_2))$. Furthermore, $N \cap \text{At}(\mathbb{P}_1 \sqcup \mathbb{P}_2) = M_1 \cup M_2 = M$, and using the inverse of g we get $M = g^{-1}(N) \in \text{SM}(\mathbb{P}_1 \sqcup \mathbb{P}_2)$.

Thus we have shown $\text{SM}(\mathbb{P}_1 \sqcup \mathbb{P}_2) = \text{SM}(\mathbb{P}_1) \bowtie \text{SM}(\mathbb{P}_2)$. $\square$

Proof of Theorem 4.30

Consider SMOELS program modules $\mathbb{P}_1$ and $\mathbb{P}_2$. It is straightforward to see that Tr_{NLP} is $\sqcup$ -preserving, that is, if $\mathbb{P}_1 \sqcup \mathbb{P}_2$ is defined, then also $\text{Tr}_{\text{NLP}}(\mathbb{P}_1) \sqcup \text{Tr}_{\text{NLP}}(\mathbb{P}_2)$ is defined. The key observation is that for every edge in the dependency graph $\text{Dep}^+(\text{Tr}_{\text{NLP}}(\mathbb{P}_1) \sqcup \text{Tr}_{\text{NLP}}(\mathbb{P}_2))$ there is also an edge in $\text{Dep}^+(\mathbb{P}_1 \sqcup \mathbb{P}_2)$.¹⁰ Since $\mathbb{P}_1$ and $\mathbb{P}_2$ are mutually independent, also $\text{Tr}_{\text{NLP}}(\mathbb{P}_1)$ and $\text{Tr}_{\text{NLP}}(\mathbb{P}_2)$ are mutually independent. Furthermore, if $\mathbb{P}_1 \sqcup \mathbb{P}_2$ is defined, then $\text{Tr}_{\text{NLP}}(\mathbb{P}_1)$ and $\text{Tr}_{\text{NLP}}(\mathbb{P}_2)$ respect each other's hidden atoms. This is because new atoms are introduced only

¹⁰ It might be the case that $\text{Dep}^+(\mathbb{P}_1 \sqcup \mathbb{P}_2)$ contains some edges that are not in $\text{Dep}^+(\text{Tr}_{\text{NLP}}(\mathbb{P}_1) \sqcup \text{Tr}_{\text{NLP}}(\mathbb{P}_2))$. This happens when there is a weight rule the body of which can never be satisfied.

for $\text{Choices}(\mathbb{P}_1) \subseteq \text{At}_o(\mathbb{P}_1) \cup \text{At}_h(\mathbb{P}_1)$ and $\text{Choices}(\mathbb{P}_2) \subseteq \text{At}_o(\mathbb{P}_2) \cup \text{At}_h(\mathbb{P}_2)$, and $(\text{At}_o(\mathbb{P}_1) \cup \text{At}_h(\mathbb{P}_1)) \cap (\text{At}_o(\mathbb{P}_2) \cup \text{At}_h(\mathbb{P}_2)) = \emptyset$. Since

$$\text{Tr}_{\text{NLP}}(\mathbb{P}_1) \sqcup \text{Tr}_{\text{NLP}}(\mathbb{P}_2) = \text{Tr}_{\text{NLP}}(\mathbb{P}_1 \sqcup \mathbb{P}_2)$$

holds, Tr_{NLP} is also modular. Thus Tr_{NLP} satisfies conditions 2 and 3 in Definition 4.27.

We are left to show that

$$\text{reveal}(\mathbb{P}, H) \equiv_m \text{reveal}(\text{Tr}_{\text{NLP}}(\mathbb{P}), H)$$

for any SMOLETS program module $\mathbb{P} = \langle P, I, O, H \rangle$ and its translation $\text{Tr}_{\text{NLP}}(\mathbb{P}) = \langle R, I, O, H \cup H' \rangle$. Note that $\text{SM}(\mathbb{P}) = \text{SM}(\text{reveal}(\mathbb{P}, H))$ and $\text{SM}(\text{Tr}_{\text{NLP}}(\mathbb{P})) = \text{SM}(\text{reveal}(\text{Tr}_{\text{NLP}}(\mathbb{P}), H))$, and the additional restriction imposed by revealing is that the bijection between these sets of stable models needs to be such that their projections over $\text{At}(\mathbb{P})$, not just over $\text{At}_v(\mathbb{P})$, coincide.

We define a function $f : \text{SM}(\mathbb{P}) \rightarrow 2^{\text{At}(\text{Tr}_{\text{NLP}}(\mathbb{P}))}$ such that

$$f(M) = M \cup \{\bar{a} \mid a \in \text{Choices}(P) \setminus M\}.$$

Clearly $M = f(M) \cap \text{At}(\mathbb{P})$. We need to show that

- (i) given any $M \in \text{SM}(\mathbb{P})$, $f(M) \in \text{SM}(\text{Tr}_{\text{NLP}}(\mathbb{P}))$; and
- (ii) $f : \text{SM}(\mathbb{P}) \rightarrow \text{SM}(\text{Tr}_{\text{NLP}}(\mathbb{P}))$ is a bijection.

Note that for any atom $a \in \text{Choices}(P)$, it holds that $\bar{a} \in f(M)$ if and only if $a \notin M$ if and only if $a \notin f(M)$.

- (i) We show that $N = f(M) \in \text{SM}(\text{Tr}_{\text{NLP}}(\mathbb{P}))$ for any $M \in \text{SM}(\mathbb{P})$:

Assume first $N \not\models R^{N,I}$, that is, there is a rule $r \in R^{N,I}$ that is not satisfied by N . If $\text{Head}(r) \in \text{At}(\mathbb{P})$, then r is of the form $a \leftarrow B' \setminus I$ and there are two possibilities:

1. There is a rule $a \leftarrow B', \sim C, \sim \bar{a} \in R$ corresponding to a choice rule $\{A\} \leftarrow B', \sim C \in P$ such that $a \in A$, $\bar{a} \notin N$, $B' \cap I \subseteq N$, and $C \cap N = \emptyset$. Since $\bar{a} \notin N$ implies $a \in N$, r is satisfied in N , a contradiction.
2. There is a rule $a \leftarrow B', \sim C' \in R$ corresponding to a weight rule $r' = a \leftarrow w \leq \{B = W_B, \sim C = W_C\} \in P$ such that $B' \subseteq B$, $C' \subseteq C$, $w \leq \sum_{b \in B'} w_b + \sum_{c \in C'} w_c$, $B' \cap I \subseteq N$, and $C' \cap N = \emptyset$. Since $N \not\models r$ we must have $a \notin N$ (which implies $a \notin M$) and $B' \setminus I \subseteq N$. Thus $B' \subseteq N$ which implies $B' \subseteq M$. Moreover, $C' \cap N = \emptyset$ implies $C' \cap M = \emptyset$. But then $w \leq \sum_{b \in B' \cap M} w_b + \sum_{c \in C' \setminus M} w_c$. Since $B' \subseteq B$ and $C' \subseteq C$, we have $w \leq \sum_{b \in B \cap M} w_b + \sum_{c \in C \setminus M} w_c$ and $M \not\models r'$, a contradiction.

Otherwise each $r \in R^{N,I}$ is of the form $\bar{a}$, in which case there is a rule $\bar{a} \leftarrow \sim a \in R$ and $a \notin N$. Since $a \notin N$ implies $\bar{a} \in N$, then $N \models r$, a contradiction. Thus $N \models R^{N,I}$, and furthermore $N \setminus I \models R^{N,I}$.

Assume now $N \setminus I \neq \text{LM}(R^{N,I})$, that is, there is $N' \subset N \setminus I$ such that $N' \models R^{N,I}$. We define $M' = N' \cap \text{At}(\mathbb{P})$ and show $M' \models P^{M,I}$, which contradicts the assumption $M \setminus I = \text{LM}(P^{M,I})$, since $M' \subset M \setminus I$. Assume that there is a rule $r \in P^{M,I}$ such that $M' \not\models r$. There are two possibilities:

1. r is of the form $a \leftarrow B \setminus I$. Then there is a choice rule $\{A\} \leftarrow B, \sim C \in P$, such that $B \cap I \subseteq M$, $C \cap M = \emptyset$, and $a \in M \cap A$. Now, $B \cap I \subseteq M$ implies $B \cap I \subseteq N$, $C \cap M = \emptyset$ implies $C \cap N = \emptyset$, and $a \in M$ implies $a \in N$ and $\bar{a} \notin N$. Together with $\{A\} \leftarrow B, \sim C \in P$ these imply $r \in R^{N,I}$. Since $M' \not\models r$, we have $a \notin M'$ and $B \setminus I \subseteq M'$. But, since $N' \cap \text{At}(\mathbb{P}) = M'$, this implies $N' \not\models r$, a contradiction to $N' \models R^{N,I}$.
2. r is of the form $a \leftarrow w' \leq \{B \setminus I = W_{B \setminus I}\}$. Then there is a weight rule $a \leftarrow w \leq \{B = W_B, \sim C = W_C\} \in P$ such that

$$w' = \max(0, w - \sum_{b \in B \cap I \cap M} w_b - \sum_{c \in C \setminus M} w_c).$$

Since $M' \not\models r$, we have $a \notin M'$ and $w' \leq \sum_{b \in (B \setminus I) \cap M'} w_b$. Define $B' = (B \cap I \cap M) \cup ((B \setminus I) \cap M')$ and $C' = C \setminus M$, and recall that $N' \cap \text{At}(\mathbb{P}) = M'$. Now $w \leq \sum_{b \in B'} w_b + \sum_{c \in C'} w_c$, $C' \cap N = \emptyset$, $B' \cap I \subseteq N$, $B' \setminus I \subseteq N'$ and $a \notin N'$, which implies that there is a rule $r' = a \leftarrow B' \setminus I \in R^{N,I}$ such that $N' \not\models r'$ which is in contradiction with $N' \models R^{N,I}$.

Thus assuming that there is $N' \subset N \setminus I$ such that $N' \models R^{N,I}$ leads to a contradiction, and it holds that $N \setminus I = \text{LM}(R^{N,I})$, that is, $N \in \text{SM}(\text{Tr}_{\text{NLP}}(\mathbb{P}))$.

(ii) *We show that $f : \text{SM}(\mathbb{P}) \rightarrow \text{SM}(\text{Tr}_{\text{NLP}}(\mathbb{P}))$ is a bijection:*

Clearly f is an injection: $M \neq M'$ implies $f(M) \neq f(M')$. To show that f is a surjection, we consider an arbitrary $N \in \text{SM}(\text{Tr}_{\text{NLP}}(\mathbb{P}))$ and show $N \cap \text{At}(\mathbb{P}) = M \in \text{SM}(\mathbb{P})$ and $f(M) = f(N \cap \text{At}(\mathbb{P})) = N$.

- Assume first $M \not\models P^{M,I}$, that is, there is a rule $r \in P^{M,I}$ that is not satisfied. Notice that all the rules in $P^{M,I}$ corresponding to a choice rule in P are always satisfied in M . Thus we need to consider only rules that correspond to a weight rule in P . Now, $r = a \leftarrow w' \leq \{B \setminus I = W_{B \setminus I}\} \in P^{M,I}$, if there is a weight rule $a \leftarrow w \leq \{B = W_B, \sim C = W_C\} \in P$ such that $w' = \max(0, w - \sum_{b \in B \cap M \cap I} w_b - \sum_{c \in C \setminus M} w_c)$. Since $M \not\models r$, then $a \notin M$ and $w' \leq \sum_{b \in (B \setminus I) \cap M} w_b$. Define $B' = B \cap M$ and $C' = C \setminus M$. Since $N \cap \text{At}(\mathbb{P}) = M$ and $w \leq \sum_{b \in B'} w_b + \sum_{c \in C'} w_c$, there is a normal rule $a \leftarrow B', \sim C' \in R$. Furthermore, $C' \cap N = \emptyset$ and $B' \cap I \subseteq N$ imply $r' = a \leftarrow B' \setminus I \in R^{N,I}$. Since $a \notin M$, also $a \notin N$. Furthermore, $B' \setminus I \subseteq M \subseteq N$. These imply $N \not\models r'$ which leads to a contradiction. Thus $M \models r$, and moreover $M \models P^{M,I}$.
- Next, assume that there is $M' \subset M \setminus I$ such that $M' \models P^{M,I}$ and define $N' = M' \cup (N \setminus \text{At}(\mathbb{P})) \subset N \setminus I$. Since $N' \setminus \text{At}(\mathbb{P}) = N \setminus \text{At}(\mathbb{P})$ by definition, each rule of the form $\bar{a} \in R^{N,I}$ is satisfied in N' . Other rules in $R^{N,I}$ are of the form $r = a \leftarrow B' \setminus I$ where $a \in \text{At}(\mathbb{P})$. There are now two possibilities.
 1. There is a choice rule $\{A\} \leftarrow B', \sim C \in P$, such that $a \in A$, $B' \cap I \subseteq N$, $C \cap N = \emptyset$, and $\bar{a} \notin N$. Now, $M \cap \text{At}(\mathbb{P}) = N \cap \text{At}(\mathbb{P})$ implies $r \in P^{M,I}$, and furthermore, $M' \models P^{M,I}$ implies $M' \models r$. Recalling $M' \cap \text{At}(\mathbb{P}) = N' \cap \text{At}(\mathbb{P})$, we get $N' \models r$.
 2. There is a rule $a \leftarrow B', \sim C' \in R$ corresponding to a weight rule $a \leftarrow w \leq \{B = W_B, \sim C = W_C\} \in P$ such that $B' \subseteq B$, $C' \subseteq C$, $w \leq \sum_{b \in B'} w_b + \sum_{c \in C'} w_c$, $B' \cap I \subseteq N$ and $C' \cap N = \emptyset$. If $B' \setminus I \not\subseteq N'$, then $N' \models r$.

Assume that $B' \setminus I \subseteq N'$. It follows from $B' \subseteq B$ and $C' \subseteq C$ that

$$w \leq \sum_{b \in (B \setminus I) \cap N'} w_b + \sum_{b \in B \cap I \cap N} w_b + \sum_{c \in C \setminus N} w_c.$$

Since $M \cap \text{At}(\mathbb{P}) = N \cap \text{At}(\mathbb{P})$, there is $r' = a \leftarrow w' \leq \{B \setminus I = W_{B \setminus I}\} \in P^{M,I}$ such that $w' = \max(0, w - \sum_{b \in B \cap I \cap M} w_b + \sum_{c \in C \setminus M} w_c)$. Furthermore, $w' \leq \sum_{b \in (B \setminus I) \cap M'} w_b = \sum_{b \in (B \setminus I) \cap N'} w_b$. Since $M' \models r'$, we have $a \in M'$, and also $a \in N'$. Thus $N' \models r$.

Thus using the assumption $M \setminus I \neq \text{LM}(P^{M,I})$ we can show that there is $N' \subset N \setminus I$ such that $N' \models R^{N,I}$, which leads to a contradiction with $N \setminus I = \text{LM}(R^{N,I})$. Therefore, $M \setminus I = \text{LM}(P^{M,I})$.

— Finally, we show that $f(M) = f(N \cap \text{At}(\mathbb{P})) = N$. Let $N' = f(M)$, that is,

$$N' = M \cup \{\bar{a} \mid a \in \text{Choices}(P) \setminus M\}.$$

Notice that $N \cap \text{At}(\mathbb{P}) = N' \cap \text{At}(\mathbb{P}) = M$. Assume $N \not\subseteq N'$, that is, there is $\bar{a} \in N$ such that $\bar{a} \notin N'$. Since $\bar{a} \notin N'$, we have $a \in N'$ and furthermore $a \in N$. The only rule r in R such that $\bar{a} = \text{Head}(r)$ is $\bar{a} \leftarrow \sim a$. However, if $a \in N$, there is no rule in $R^{N,I}$ in which $\bar{a}$ appears in the head. Because $N \setminus I$ is the least model of $R^{N,I}$, we have $\bar{a} \notin N$, a contradiction. Assume then $N' \not\subseteq N$, that is, there is $\bar{a} \in N'$ such that $\bar{a} \notin N$. Since $\bar{a} \in N'$, we have $a \notin N'$ and furthermore $a \notin N$. If $a \notin N$, then $\bar{a} \in R^{N,I}$. Since $N \setminus I \models R^{N,I}$, we must have $\bar{a} \in N$, a contradiction. Therefore it holds that $N = N'$.

Thus we have shown that Tr_{NLP} is a strongly faithful, $\sqcup$ -preserving, and modular translation function. $\square$

References

- BARAL, C. 2003. *Knowledge Representation, Reasoning and Declarative Problem Solving*. Cambridge University Press.
- BRAIN, M., CRICK, T., VOS, M. D., AND FITCH, J. 2006. TOAST: Applying answer set programming to superoptimisation. In *Logic Programming: 22nd International Conference, ICLP 2006, Seattle, WA, USA, August 2006, Proceedings*, S. Etalle and M. Truszczynski, Eds. Lecture Notes in Computer Science, vol. 4079. Springer, 270–284.
- BROGI, A., MANCARELLA, P., PEDRESCHI, D., AND TURINI, F. 1994. Modular logic programming. *ACM Transactions on Programming Languages and Systems* 16, 4, 1361–1398.
- BROOKS, D. R., ERDEM, E., ERDOGAN, S. T., MINETT, J. W., AND RINGE, D. 2007. Inferring phylogenetic trees using answer set programming. *Journal of Automated Reasoning* 39, 4, 471–511.
- BUGLIESI, M., LAMMA, E., AND MELLO, P. 1994. Modularity in logic programming. *Journal of Logic Programming* 19/20, 443–502.
- CLARK, K. L. 1978. Negation as failure. In *Logic and Data Bases*, H. Gallaire and J. Minker, Eds. Plenum Press, New York, 293–322.
- EITER, T. AND FINK, M. 2003. Uniform equivalence of logic programs under the stable model semantics. In *Logic Programming: 19th International Conference, ICLP 2003*,

- Mumbai, India, December 2003, *Proceedings*, C. Palamidessi, Ed. Lecture Notes in Computer Science, vol. 2916. Springer, 224–238.
- EITER, T., FINK, M., TOMPITS, H., AND WOLTRAN, S. 2004. Simplifying logic programs under uniform and strong equivalence. In *Logic Programming and Nonmonotonic Reasoning: 7th International Conference, LPNMR 2004, Fort Lauderdale, FL, USA, January 2004, Proceedings*, V. Lifschitz and I. Niemelä, Eds. Lecture Notes in Artificial Intelligence, vol. 2923. Springer, 87–99.
- EITER, T., GOTTLÖB, G., AND MANNILA, H. 1997. Disjunctive datalog. *ACM Transactions on Database Systems* 22, 3, 364–418.
- EITER, T., GOTTLÖB, G., AND VEITH, H. 1997. Modular logic programming and generalized quantifiers. In *Logic Programming and Nonmonotonic Reasoning: 4th International Conference, LPNMR'97, Dagstuhl Castle, Germany, July 1997, Proceedings*, J. Dix, U. Furbach, and A. Nerode, Eds. Lecture Notes in Artificial Intelligence, vol. 1265. Springer, 290–309.
- EITER, T., TOMPITS, H., AND WOLTRAN, S. 2005. On solution correspondences in answer-set programming. In *IJCAI-05, Proceedings of the Nineteenth International Joint Conference on Artificial Intelligence, Edinburgh, Scotland, UK, July-August 2005*, L. P. Kaelbling and A. Saffioti, Eds. Professional Book Center, 97–102.
- ERDEM, E., LIFSCHITZ, V., AND RINGE, D. 2006. Temporal phylogenetic networks and logic programming. *Theory and Practice of Logic Programming* 6, 5, 539–558.
- ETALLE, S. AND GABBRIELLI, M. 1996. Transformations of CLP modules. *Theoretical Computer Science* 166, 1&2, 101–146.
- FABER, W., GRECO, G., AND LEONE, N. 2005. Magic sets and their application to data integration. In *Database Theory - ICDT 2005: 10th International Conference, Edinburgh, UK, January 2005, Proceedings*, T. Eiter and L. Libkin, Eds. Lecture Notes in Computer Science, vol. 3363. Springer, 306–320.
- FAGES, F. 1994. Consistency of Clark's completion and existence of stable models. *Journal of Methods of Logic in Computer Science* 1, 51–60.
- FERRARIS, P. AND LIFSCHITZ, V. 2005. Weight constraints as nested expressions. *Theory and Practice of Logic Programming* 5, 1-2, 45–74.
- GAIFMAN, H. AND SHAPIRO, E. Y. 1989. Fully abstract compositional semantics for logic programs. In *Conference Record of the Sixteenth Annual ACM SIGACT-SIGPLAN Symposium on Principles of Programming Languages*. ACM Press, Austin, Texas, USA, 134–142.
- GEBSER, M., KAUFMANN, B., NEUMANN, A., AND SCHAUB, T. 2007. CLASP : A conflict-driven answer set solver. In *Logic Programming and Nonmonotonic Reasoning: 9th International Conference, LPNMR 2007, Tempe, AZ, USA, May 2007, Proceedings*, C. Baral, G. Brewka, and J. S. Schlipf, Eds. Lecture Notes in Artificial Intelligence, vol. 4483. Springer, 260–265.
- GELFOND, M. AND GABALDON, A. 1999. Building a knowledge base: an example. *Annals of Mathematics and Artificial Intelligence* 25, 3-4, 165–199.
- GELFOND, M. AND LEONE, N. 2002. Logic programming and knowledge representation - the A-Prolog perspective. *Artificial Intelligence* 138, 1-2, 3–38.
- GELFOND, M. AND LIFSCHITZ, V. 1988. The stable model semantics for logic programming. In *Logic Programming: Proceedings of the Fifth International Conference and Symposium, Seattle, Washington, August 1988*, R. A. Kowalski and K. A. Bowen, Eds. MIT Press, 1070–1080.
- GELFOND, M. AND LIFSCHITZ, V. 1990. Logic programs with classical negation. In *Logic programming: Proceedings of the 7th International Conference, Jerusalem, Israel, June 1990*, D. H. D. Warren and P. Szeredi, Eds. MIT Press, 579–597.

- GIORDANO, L. AND MARTELLI, A. 1994. Structuring logic programs: A modal approach. *Journal of Logic Programming* 21, 2, 59–94.
- HELJANKO, K. AND ȘTEFĂNESCU, A. 2004. Complexity results for checking distributed implementability. Technical Report 05/2004, Institute of Formal Methods in Computer Science, University of Stuttgart, Stuttgart, Germany.
- HELJANKO, K. AND ȘTEFĂNESCU, A. 2005. Complexity results for checking distributed implementability. In *Fifth International Conference on Application of Concurrency to System Design, ACSD 2005, St. Malo, France, June 2005, Proceedings*, J. Desel and Y. Watanabe, Eds. IEEE Computer Society, 78–87.
- IANNI, G., IELPA, G., PIETRAMALA, A., SANTORO, M. C., AND CALIMERI, F. 2004. Enhancing answer set programming with templates. In *10th International Workshop on Non-Monotonic Reasoning (NMR 2004), Whistler, Canada, June 2004, Proceedings*, J. P. Delgrande and T. Schaub, Eds. 233–239.
- JAFFAR, J. AND MAHER, M. J. 1994. Constraint logic programming: A survey. *Journal of Logic Programming* 19/20, 503–581.
- JANHUNEN, T. 2006. Some (in)translatability results for normal logic programs and propositional theories. *Journal of Applied Non-Classical Logics* 16, 1-2, 35–86.
- JANHUNEN, T. 2007. Intermediate languages of ASP systems and tools. In *Proceedings of the 1st International Workshop on Software Engineering for Answer Set Programming*, M. De Vos and T. Schaub, Eds. Number CSBU-2007-05 in Department of Computer Science, University of Bath, Technical Report Series. Tempe, Arizona, USA, 12–25.
- JANHUNEN, T. AND OIKARINEN, E. 2002. Testing the equivalence of logic programs under stable model semantics. In *Logics in Artificial Intelligence, 8th European Conference, JELIA 2002, Cosenza, Italy, September 2002, Proceedings*, S. Flesca, S. Greco, N. Leone, and G. Ianni, Eds. Lecture Notes in Artificial Intelligence, vol. 2424. Springer, 493–504.
- JANHUNEN, T. AND OIKARINEN, E. 2007. Automated verification of weak equivalence within the SMOELS system. *Theory and Practice of Logic Programming* 7, 6, 697–744.
- JANHUNEN, T., OIKARINEN, E., TOMPITS, H., AND WOLTRAN, S. 2007. Modularity aspects of disjunctive stable models. In *Logic Programming and Nonmonotonic Reasoning: 9th International Conference, LPNMR 2007, Tempe, AZ, USA, May 2007, Proceedings*, C. Baral, G. Brewka, and J. Schlipf, Eds. Lecture Notes in Artificial Intelligence, vol. 4483. Springer, 175–187.
- JÄRVISALO, M. AND OIKARINEN, E. 2007. Extended ASP tableaux and rule redundancy in normal logic programs. In *Logic Programming: 23rd International Conference, ICLP 2007, Porto, Portugal, September 2007, Proceedings*, V. Dahl and I. Niemelä, Eds. Lecture Notes in Computer Science, vol. 4670. Springer, 134–148.
- LIERLER, Y. 2005. cMODELS – SAT-based disjunctive answer set solver. In *Logic Programming and Nonmonotonic Reasoning, 8th International Conference, LPNMR 2005, Diamante, Italy, September 2005, Proceedings*, C. Baral, G. Greco, N. Leone, and G. Terracina, Eds. Lecture Notes in Artificial Intelligence, vol. 3662. Springer, 447–451.
- LIFSCHITZ, V. 1985. Computing circumscription. In *Proceedings of the Ninth International Joint Conference on Artificial Intelligence, 18–23 August 1985, Los Angeles, California*, A. K. Joshi, Ed. Morgan Kaufmann, 121–127.
- LIFSCHITZ, V., PEARCE, D., AND VALVERDE, A. 2001. Strongly equivalent logic programs. *ACM Transactions on Computational Logic* 2, 4, 526–541.
- LIFSCHITZ, V. AND TURNER, H. 1994. Splitting a logic program. In *Logic Programming: Proceedings of the Eleventh International Conference on Logic Programming, June 1994, Santa Margherita Ligure, Italy*, P. V. Hentenryck, Ed. MIT Press, 23–37.
- LIN, F. AND ZHAO, Y. 2004. ASSAT: Computing answer sets of a logic program by SAT solvers. *Artificial Intelligence* 157, 1-2, 115–137.

- MAHER, M. J. 1993. A transformation system for deductive database modules with perfect model semantics. *Theoretical Computer Science* 110, 2, 377–403.
- MANCARELLA, P. AND PEDRESCHI, D. 1988. An algebra of logic programs. In *Logic Programming: Proceedings of the Fifth International Conference and Symposium, Seattle, Washington, August 1988*, R. A. Kowalski and K. A. Bowen, Eds. MIT Press, 1006–1023.
- MAREK, V. W. AND TRUSZCZYŃSKI, M. 1991. Autoepistemic logic. *Journal of the ACM* 38, 3, 588–619.
- MAREK, V. W. AND TRUSZCZYŃSKI, M. 1999. Stable models and an alternative logic programming paradigm. In *The Logic Programming Paradigm: a 25-Year Perspective*, K. R. Apt, V. W. Marek, M. Truszczyński, and D. S. Warren, Eds. Springer, 375–398.
- MEYER, A. R. 1988. Semantical paradigms: Notes for an invited lecture, with two appendices by Stavros S. Cosmadakis. In *Proceedings, 3rd Annual Symposium on Logic in Computer Science, 5-8 July 1988, Edinburgh, Scotland, UK*, Y. Gurevich, Ed. IEEE Computer Society, 236–253.
- MILLER, D. 1989. A logical analysis of modules in logic programming. *Journal of Logic Programming* 6, 1–2, 79–108.
- MOSTOWSKI, A. 1957. On a generalization of quantifiers. *Fundamenta Mathematicae* 44, 12–36.
- NIEMELÄ, I. 1999. Logic programming with stable model semantics as a constraint programming paradigm. *Annals of Mathematics and Artificial Intelligence* 25, 3-4, 241–273.
- NOGUEIRA, M., BALDUCCINI, M., GELFOND, M., WATSON, R., AND BARRY, M. 2001. An A-Prolog decision support system for the space shuttle. In *Practical Aspects of Declarative Languages, Third International Symposium, PADL 2001, Las Vegas, Nevada, March 2001, Proceedings*, I. V. Ramakrishnan, Ed. Lecture Notes in Computer Science, vol. 1990. Springer, 169–183.
- OIKARINEN, E. 2007. Modularity in smodels programs. In *Logic Programming and Non-monotonic Reasoning: 9th International Conference, LPNMR 2007, Tempe, AZ, USA, May 2007, Proceedings*, C. Baral, G. Brewka, and J. Schlipf, Eds. Lecture Notes in Artificial Intelligence, vol. 4483. Springer, 321–326.
- OIKARINEN, E. AND JANHUNEN, T. 2006. Modular equivalence for normal logic programs. In *ECAI 2006, 17th European Conference on Artificial Intelligence, August 29 – September 1, 2006, Riva del Garda, Italy, Proceedings*, G. Brewka, S. Coradeschi, A. Perini, and P. Traverso, Eds. IOS Press, 412–416.
- OIKARINEN, E. AND JANHUNEN, T. 2008a. Implementing prioritized circumscription by computing disjunctive stable models. In *Artificial Intelligence: Methodology, Systems, and Applications, 13th International Conference, AIMS 2008, Varna, Bulgaria, September 2008 Proceedings*, D. Dochev, M. Pistore, and P. Traverso, Eds. Lecture Notes in Artificial Intelligence, vol. 5223. Springer, 167–180.
- OIKARINEN, E. AND JANHUNEN, T. 2008b. A translation-based approach to the verification of modular equivalence. *Journal of Logic and Computation*, to appear.
- O'KEEFE, R. A. 1985. Towards an algebra for constructing logic programs. In *Proceedings of the 1985 Symposium on Logic Programming*. Boston, Massachusetts, USA, 152–160.
- PEARCE, D., TOMPITS, H., AND WOLTRAN, S. 2001. Encodings for equilibrium logic and logic programs with nested expressions. In *Progress in Artificial Intelligence, Knowledge Extraction, Multi-agent Systems, Logic Programming and Constraint Solving, 10th Portuguese Conference on Artificial Intelligence, EPIA 2001, Porto, Portugal, December 2001, Proceedings*, P. Brazdil and A. Jorge, Eds. Lecture Notes in Artificial Intelligence, vol. 2258. Springer, 306–320.
- PRZYMUSINSKI, T. C. 1988. Perfect model semantics. In *Logic Programming: Proceedings of the Fifth International Conference and Symposium, Seattle, Washington, August 1988*, R. A. Kowalski and K. A. Bowen, Eds. MIT Press, 1081–1096.

- SAGIV, Y. 1987. Optimizing datalog programs. In *Proceedings of the Sixth ACM SIGACT-SIGMOD-SIGART Symposium on Principles of Database Systems, March 1987, San Diego, California*. ACM Press, 349–362.
- SIMONS, P., NIEMELÄ, I., AND SOININEN, T. 2002. Extending and implementing the stable model semantics. *Artificial Intelligence* 138, 1-2, 181–234.
- SOININEN, T., NIEMELÄ, I., TIIHONEN, J., AND SULONEN, R. 2001. Representing configuration knowledge with weight constraint rules. In *Proceedings of the 1st International Workshop on Answer Set Programming: Towards Efficient and Scalable Knowledge (ASP 2001)*, A. Proveti and T. C. Son, Eds. AAAI Press, Stanford, USA.
- TARI, L., BARAL, C., AND ANWAR, S. 2005. A language for modular answer set programming: Application to ACC tournament scheduling. In *Answer Set Programming, Advances in Theory and Implementation, Proceedings of the 3rd International ASP'05 Workshop, Bath, UK, September 2005*, M. D. Vos and A. Proveti, Eds. CEUR Workshop Proceedings, vol. 142. CEUR-WS.org.
- TARJAN, R. 1972. Depth-first search and linear graph algorithms. *SIAM Journal on Computing* 1, 2, 146–160.
- TURNER, H. 2003. Strong equivalence made easy: Nested expressions and weight constraints. *Theory and Practice of Logic Programming* 3, 4–5, 609–622.
- VALIANT, L. G. 1979. The complexity of enumeration and reliability problems. *SIAM Journal on Computing* 8, 3, 410–421.
- WOLTRAN, S. 2004. Characterizations for relativized notions of equivalence in answer set programming. In *Logics in Artificial Intelligence: 9th European Conference, JELIA 2004, Lisbon, Portugal, September 2004, Proceedings*, J. J. Alferes and J. A. Leite, Eds. Lecture Notes in Artificial Intelligence, vol. 3229. Springer, 161–173.
- WOLTRAN, S. 2007. A common view on strong, uniform, and other notions of equivalence in answer-set programming. In *Proceedings of the LPNMR'07 Workshop on Correspondence and Equivalence for Nonmonotonic Theories (CENT2007), Tempe, AZ, USA, May 2007*, D. Pearce, A. Polleres, A. Valverde, and S. Woltran, Eds. CEUR Workshop Proceedings, vol. 265. CEUR-WS.org, 13–24.